



JUNO

PAINT MANUFACTURERS SINCE 1927

Product Catalogue

2026 / 2027

DECORATION
CONSTRUCTION
RESTORATION

Professional and decorative
paints and coatings.

Due to limitations with the printing process, colour swatches and images are for inspiration purposes only. The colour swatches do not exactly match the paint colour in the can. Colour chips in product colour cards will be much more accurate, but slight variations between batches of paint may occur.

Where more than one tin of paint is required, check that batch numbers are identical, and if not, intermix before use.

Please ensure a tester is used on the actual surface to be painted before decoration.

This catalogue and the images and information herein is the property of JUNO and may not be copied or reproduced without the express authorisation of JUNO. Unauthorised reproduction is protected by law. Any consultation and authorisation to use this catalogue must be sent to JUNO (export@juno.es).

INDEX

EXTERIOR

Exterior house paint and masonry surfaces	5
High Build masonry coatings	7
Acrylic renders	8
Specialist exterior coatings	9
Exterior sealers & primers	11
Hydrophobic treatment	11

WATERPROOFING

Horizontal waterproofing	13
Façades & vertical waterproofing	14

INTERIOR

Interior emulsions	16
Trade emulsions ideal for spraying	17
Specialist interior paints	17
AENOR certified washable paints	18
Interior tinting bases	18
Sealers	19
Stain blocks	20

FLOOR COATINGS

1K Floor coatings	22
2K Floor coatings	22
Microbeads	24
100% Solids 2K Epoxy system	24
Pool/Milking parlour/Traffic Marking	25
Line marking for grass/turf	25

TRIM PAINT

Solvent-based enamels	27
Water-based enamels	29
Tinting bases - Decorative	30
Tinting bases - Industrial	30
Adhesion & anti-corrosive primers	31
Wood primers	31

WOOD COATINGS

Undercoats and preparation	33
Water-based varnishes	33
Solvent-based varnishes	34

SUNDRIES

Fillers & caulk	36
Colourants, paint stripper, additives, etc	37
Thinners & cleaners	39
Colour charts & fan decks	39

SUPPLEMENTARY PRODUCTS

Special exterior coatings	41
Special interior coatings	42
Water-based 2K polyurethane	43
Sealers/primers	43
Thinners	43
2K Clear polyurethane	44
Colourants - Tinting System	44

MARKETED PRODUCT RANGE

Intumescent paints	46
--------------------	----



EXTERIOR

Exterior house paint and masonry surfaces · High Build masonry coatings · Acrylic renders · Specialist exterior coatings · Exterior sealers and primers · Hydrophobic treatment

Exterior house paint and masonry surfaces

NOVOKRIL
Satin



NEW ANTI-SPLATTER TECHNOLOGY
In upcoming production runs.

Matt



NEW ANTI-SPLATTER TECHNOLOGY
In upcoming production runs.

JUNO Façades Colour CARD
JUNOMATIC Tinting System

Premium performance microporous and breathable masonry coating. With anti-mould protection.
100% pure acrylic resin, formulated with advanced technology pure acrylic copolymers for great flexibility and adhesion that make it resistant to rain water and permeable to water vapour, allowing moisture and air to be released.
For exterior use.
Cleaning and dilution with water.

Recommended for decorating and waterproofing masonry surfaces such as cement and concrete materials (façades, walls, patios, etc.) and any surface that requires maximum resistance to atmospheric agents and humid environments.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Pull-off adhesion - Permeability to rain water and water vapour - Anti-carbonation - Fire retardant to B-s1,d0 standard.

EPD®
THE INTERNATIONAL EPD SYSTEM

	ADHESION	PERMEABILITY	ANTI-CARBONATION	FIRE-RETARDANT B-s1,d0
Satin finish				
White base/P (62.150)		•		•
Medium base/D (62.169)		•		•
Deep base/TR (62.170)		•		•
Matt finish				
White base/P (62.195)		•		•
Medium base/D (62.145)		•		•
Deep base/TR (62.146)		•		•

15 l

4 l

JUNOKRIL
Satin



NEW ANTI-SPLATTER TECHNOLOGY
In upcoming production runs.

Matt



NEW ANTI-SPLATTER TECHNOLOGY

JUNO Façades Colour CARD
JUNOKRIL Colour CARD
JUNOMATIC Tinting System

High performance microporous and breathable paint. With anti-mould protection.
Formulated with acrylic-vinyl copolymers (satin finish) or pure acrylic resins (matt finish) with anti-carbonation properties. Resistant to rain water and permeable to water vapours, allowing moisture and air to be released. Wide range of tinting bases for optimal performance, colour stability and opacity.
For exterior use.

Recommended for decorating and waterproofing masonry surfaces such as cement and concrete materials (façades, walls, patios, etc.) and any surface that requires maximum resistance to atmospheric agents and humid environments. Matt finish valid as topcoat in the JUNOTherm® ETICS system.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - CE Certified: Direct pull-off adhesion - Permeability to rain water and water vapour - Anti-carbonation - Fire retardant to B-s1,d0 standard.

EPD®
THE INTERNATIONAL EPD SYSTEM

CE

	ADHESION	PERMEABILITY	ANTI-CARBONATION	FIRE-RETARDANT B-s1,d0
Satin finish				
White base/P (61.000)		•		•
Black* (61.001)		•		•
Ochre* (61.065)		•		•
Turkish red* (61.070)		•		•
Txoko brown* (61.071)		•		•
Pelota court green* (61.052)		•		•
Blue* (61.012)		•		•
Red* (61.016)		•		•
Yellow* (61.025)		•		•
Medium base/D (61.195)		•		•
Deep base/TR (61.196)		•		•
Matt finish				
White base/P (60.500)		•		•
Medium base/D (60.501)		•		•
Deep base/TR (60.502)		•		•
Yellow base/GL* (88.895)		•		•
Red base/ RD* (88.896)		•		•

15 l

4 l

750 ml

BIKRIL

Satin



In upcoming production runs.

Silk



In upcoming production runs.

Matt



In upcoming production runs.



High quality microporous and breathable water-based paint, special for decoration. With anti-mould protection.

Formulated with high quality resins, with anti-carbonation properties. Quick drying formulation resistant to rain water and permeable to water vapour allowing moisture and air to be released. For exterior and interior use.

Cleaning and dilution with water.

Recommended for decorating and waterproofing masonry surfaces such as cement and concrete materials. Also ideal for kitchens, bathrooms and other areas exposed to contact with water, humidity, etc. Matt finish valid as topcoat in the JUNOTherm® ETICS system.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - CE (only matt finish): Direct pull-off adhesion - Permeability to rain water and water vapour - Anti-carbonation - Fire retardant to B-s1,d0 standard.



Satin finish

	15 l	4 l	750 ml
<input type="checkbox"/> White base/P (60.100)	•	•	•
Medium base/D (60.101)	•	•	•
Deep base/TR (60.102)	•	•	•

Silk finish

	15 l	4 l	750 ml
<input type="checkbox"/> White base/P (60.400)	•	•	•
Medium base/D (60.401)	•	•	•
Deep base/TR (60.402)	•	•	•

Matt finish

	15 l	4 l	750 ml
<input type="checkbox"/> White base/P (60.300)	•	•	•
Medium base/D (60.301)	•	•	•
Deep base/TR (60.302)	•	•	•

J-300

High Satin



High satin finish emulsion. With anti-mould protection.

Formulated in dispersion using Veova vinyl resins.

For exterior and interior use.

Cleaning and dilution with water.

Recommended for general use in construction on plaster, cement surfaces, etc. Good whiteness, hiding power and easy application. Resistant to wet rubbing and scuffing and permeable to water vapour, allowing moisture and air to be released.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.



	15 l	4 l
<input type="checkbox"/> White (71.055)	•	•

J-3000

Medium Satin



Medium satin finish emulsion. With anti-mould protection.

Formulated with resins in aqueous dispersion.

For exterior and interior use.

Cleaning and dilution with water.

Recommended for general use in construction on plaster, cement surfaces, etc. Good whiteness, hiding power and easy application.

Resistant to wet rubbing and scuffing and permeable to water vapour, allowing moisture and air to be released.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.



	15 l	4 l
<input type="checkbox"/> White (71.063)	•	•

A-100 STIMAX

Matt



High performance water-based acrylic paint. With anti-mould protection.

Formulated with 100% acrylic resins in aqueous dispersion, titanium dioxide and extenders. For exterior and interior use. Cleaning and dilution with water.

Recommended for decorating façades, walls and for interiors and spaces where a quality matt finish, resistant to water and permeable to water vapour is required, allowing moisture and air to be released.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.



	15 l	4 l	750 ml
<input type="checkbox"/> White (62.400)	•	•	•

A-5000
Matt



Professional, high-performance water-based paint for use in mild climates. Contains anti-mould preservatives.

Formulated with styrene-acrylic resins in aqueous dispersion. Suitable for both interior and exterior applications. Clean tools and dilute with water.

EPD®
THE INTERNATIONAL EPD® SYSTEM

White (62.590)

Recommended for the decoration of façades, patios, warehouses, and other areas where a high-quality finish is required at a competitive price.

APPROVAL CERTIFICATES: EPD (Certified with an Environmental Product Declaration) - Reaction to fire classification: B-s1,d0.

15 l **4 l**

High Build masonry coatings

SUPER JUNOREV
Matt / Smooth



NEW ANTI-SPLATTER TECHNOLOGY
In upcoming production runs.

JUNO Façades Colour CARD
JUNOMATIC Tinting System

Premium high build masonry coating. With anti-mould protection.

Formulated with the highest quality acrylic copolymers in aqueous dispersion providing excellent outdoor performance. Super Junorev is microporous and breathable allowing moisture and air to be released. For exterior and interior use. Cleaning and dilution with water.

EPD®
THE INTERNATIONAL EPD® SYSTEM

Smooth finish

White base/P (65.101)

Medium base/D (65.215)

Deep base/TR (65.216)

Recommended for protecting and decorating mineral surfaces, including renders and pebbledash, in need of protection from rain, humidity, micro-organisms and carbonation. Super Junorev actively resists peeling and flaking.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - CE: Direct pull-off adhesion - Permeability to rain water and water vapour - Anti-carbonation - Fire retardant to B-s1,d0 standard.

15 l **4 l**

JUNOREV
Matt / Smooth



Matt / Textured



JUNO Façades Colour CARD
JUNOREV Colour CARD

100% acrylic high build masonry coating. With anti-mould protection.

Formulated with acrylic resins in aqueous dispersion with excellent mechanical properties. Junorev is both microporous and breathable allowing moisture and air to be released. For exterior and interior use. Cleaning and dilution with water.

EPD®
THE INTERNATIONAL EPD® SYSTEM

Smooth finish

White base/P (65.500)

<input checked="" type="checkbox"/> Grey* (65.502)	<input checked="" type="checkbox"/> Brick* (65.547)	<input checked="" type="checkbox"/> Pastel* (65.580)
<input checked="" type="checkbox"/> Clay* (65.515)	<input checked="" type="checkbox"/> Terracotta* (65.548)	<input checked="" type="checkbox"/> Cinnamon* (65.582)
<input checked="" type="checkbox"/> Sand* (65.521)	<input checked="" type="checkbox"/> Light beige* (65.560)	<input checked="" type="checkbox"/> Hazelnut* (65.584)
<input checked="" type="checkbox"/> Cream* (65.522)	<input checked="" type="checkbox"/> Turkish red* (65.570)	<input checked="" type="checkbox"/> Dune* (65.585)
<input checked="" type="checkbox"/> Wheat yellow* (65.530)	<input checked="" type="checkbox"/> Tile* (65.575)	
<input checked="" type="checkbox"/> Mustard yellow* (65.550)	<input checked="" type="checkbox"/> Pelota court green* (65.552)	

Textured finish

White base/P (64.500)

Recommended for protecting and decorating mineral surfaces, including renders and pebbledash, in need of protection from rain, humidity, micro-organisms and carbonation. Junorev actively resists peeling and flaking. Valid as finishing topcoat in the JUNOTherm® ETICS system.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - CE (smooth finish): Direct pull-off adhesion - Anti-carbonation - Light Stability - Permeability to rain water and water vapour - Fire retardant to B-s1,d0 standard.

15 l **4 l**

LUNA
Matt



BIKRIL/LUNA Colour CARD
JUNOMATIC Tinting System

High build masonry coating with anti-mould protection.

Formulated with styrene-acrylic resins in aqueous dispersion with excellent mechanical properties and permeable to water vapour, allowing moisture and air to be released.

For exterior and interior use.
Cleaning and dilution with water.

 EPD®
THE INTERNATIONAL EPD SYSTEM

Recommended for the protection and decoration of mineral surfaces (cement, concrete, pebbledash or renders, etc.). Ideal for correcting finishing faults and touch-ups on surfaces, providing a high opacity decorative finish.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.


15 l

<input type="checkbox"/> White base/P (67.500)		•
<input checked="" type="checkbox"/> Deep base/TR (67.501)		•

Acrylic renders

EVOKRIL BASE
Matt



ETICS System Colour Chart

Water-based pigmented acrylic copolymer primer base coating for the EVOKRIL decorative/protective render system, ETICS system - JUNOTherm® and other masonry systems.

Formulated based on water-based acrylic copolymers to consolidate, waterproof and even out the surface before applying the render. Fine-grained. Great penetrating power.

Excellent waterproofing and breathability.
For interior and exterior use.
Cleaning and thinning with water.

 EPD®
THE INTERNATIONAL EPD SYSTEM

Recommended as a primer on surfaces such as paint, cement, fibre cement, plaster, concrete, non-waterproof surfaces, etc. for EVOKRIL render system and other masonry coatings.

Improves adhesion and uniformity of successive paint coats.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).

22 kg

<input type="checkbox"/> White base/P (64.400)		•
<input checked="" type="checkbox"/> Deep base/TR (64.401)		•

EVOKRIL
Matt



ETICS System Colour Chart

Acrylic render for waterproofing and decorating façades. (0.7 mm grain size) With anti-mould protection.

Formulated based on acrylic copolymers and selected fillers to achieve a variety of decorative finishes and textures: dropfinish, floated, roughcast and scraped finish.

Great elasticity, adhesion and hardness.
Excellent waterproofing capacity and breathability.
For interior and exterior use.
Cleaning and thinning with water.

 EPD®
THE INTERNATIONAL EPD SYSTEM

Recommended to achieve decorative finishes on façades. For universal application on non-waterproof concrete, cement, plaster, fiber cement, paint, etc.

Finishing mortar for ETICS JUNOTherm® system.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - CE certified for Direct traction adhesion - Permeability to rainwater and water vapours.






	25 kg:	0.7 Grain size	1.0 Grain size	1.5 Grain size
<input type="checkbox"/> White base/P		(64.408) •	(64.424) •	(64.416) •
<input checked="" type="checkbox"/> Deep base/TR		(64.409) •	(64.425) •	(64.417) •

EVOKRIL SLX

Matt



Siloxane-based render (1.5 mm grain size) for decoration and waterproofing exterior walls. With anti-mould protection.

Formulated with modified acrylic copolymers with polysiloxanes and selected fillers to achieve a variety of decorative finishes and textures: f.ex. dropfinish, floated, roughcast scraped finish etc.

Great elasticity, adhesion and hardness.

Repels water and dirt.

Excellent waterproofing capacity and breathability. For interior and exterior use.

Cleaning and thinning with water.

Recommended to achieve decorative finishes on façades. For universal application on non-waterproof concrete, cement, plaster, fiber cement, paint, etc.

Finishing mortar for ETICS JUNOTherm® system.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - CE certified for Direct traction adhesion - Permeability to rainwater and water vapours. Fire retardant to Euroclass B-s2,d0.



New

25 kg:	1.0 Grain size	1.5 Grain size
	(64.448)	(64.440)
	(64.449)	(64.441)

White base/P

Deep base/TR



Specialist exterior coatings

Silicate & Mineral Paint System

MINERAL PRIMER

Matt



Water-based mineral primer based on potassium silicate with excellent penetration and adhesion properties.

For interior and exterior use.

Cleaning and dilution with water.

Recommended as a base coat in silicate paint systems that require binding, including protecting mineral surfaces such as lime and cement renders, gypsum plasters and stonework. Its also ideal for problematic areas such as damp basements and can also be used as a stabilising primer for powdery and friable surfaces.

For a high quality breathable paint system Silicato-Silicate Paint (75.362) is recommended as a topcoat.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).



15 l

Translucent white (75.302)

SILICATO

Matt



Highly breathable silicate paint. A matt, durable and highly breathable alternative to conventional masonry paints and limewash.

Formulated with potassium silicate, fillers, additives and inorganic pigments stable to light and weather. Chemically bonds to create a water/weather-resistant barrier.

For interior and exterior use.

Cleaning and dilution with water.

Suitable for use on stone, masonry, concrete, pebble dash, plaster and silicate paint surfaces. Perfect match for heritage projects and old buildings.


APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - A+ Certified - Meets health related evaluation procedure for emissions of VOC's (German AgBB 2018) - Fire retardant to B-s1,d0 standard.



15 l

4 l

White base/P (75.362)



Pliolite-based paints

<p>JUNOLITE FAÇADES Matt</p>  <p>JUNO Façades Colour CARD</p>	<p>Self-cleaning, breathable Pliolite paint. Junolite is a premium quality, solvent-based masonry paint formulated for exterior use. Formulated with Pliolite resins and organic solvents. Offers protection against alkalis and salt efflorescence. For exterior use. Cleaning and dilution with chlorinated rubber solvent D-40 (Code 50.000).</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p><input type="checkbox"/> White base/P (62.900)</p>	<p>Junolite provides a long lasting coating with good adhesion and resistance to moisture and alkali attack on exterior surfaces such as cement rendering, rough cast, brick and concrete.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <p>15 I</p>
<p>HYDROPLIOLITE Matt</p> 	<p>High quality water-based pliolite paint. Alkali resistant and contains anti-mould preservatives. Formulated with pliolite resins in aqueous dispersion. Providing excellent adhesion to degraded substrates, and excellent resistance to alkalis and UV rays. Interior and exterior use. Cleaning and dilution with water.</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p><input type="checkbox"/> White (62.991)</p>	<p>Recommended for protection of exterior walls, partition walls and concrete surfaces in general, where good adhesion, a matt finish and great resistance to atmospheric agents is required.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <p>15 I</p>

Water-Repellent Masonry Paints (Silicone & Siloxane)

<p>SILOX Matt</p> 	<p>Siloxane-based paint with excellent resistance to weathering. With anti-mould protection. Paint with polysiloxane resins that provide high hydrophobicity. For exterior use. Cleaning and dilution with water.</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p><input type="checkbox"/> White (62.005)</p>	<p>Recommended for painting and decorating façades where a matt finish is required. Resistant to rain water, permeable to water vapour and resistant to ultraviolet rays and the formation of mould. Valid as finishing topcoat in the JUNOTherm® ETICS system.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p>FIRE-RETARDANT B-s1,d0</p> <p>15 I</p>
<p>JUNOSIL SILICONE-MODIFIED PAINT Matt</p> 	<p>Silicone water-based paint. Paint with acrylic copolymers and silicone additives. Water-based silicone-modified masonry paint. For interior and exterior use. Cleaning and dilution with water.</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p><input type="checkbox"/> White (73.160)</p>	<p>Especially recommended for painting and decorating lime-coated surfaces, thanks to its excellent whiteness and opacity.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p>FIRE-RETARDANT B-s1,d0</p> <p>15 I</p>

Exterior sealers & primers

<p>HIDROCRIL Semi-matt</p> 	<p>Hidrocril – Penetrating Acrylic water-based Sealer & Binding Primer. Concentrated water-based acrylic sealer designed to penetrate, bind and stabilise porous or powdery surfaces. Suitable for interior and exterior use, it provides outstanding adhesion and creates a sound surface for subsequent decoration.</p> <ul style="list-style-type: none"> - Deep-penetrating formula that consolidates porous and friable substrates - Binds chalky, powdery or unstable surfaces - Promotes excellent adhesion for topcoats - Equalises surface porosity for a uniform finish - Water-based – low odour and easy clean-up - Dilutable concentrate (mixing ratio 4:1 – Water: Hidrocril) <p> THE INTERNATIONAL EPD SYSTEM</p> <p><input checked="" type="checkbox"/> Clear/Transparent (81.006)</p>	<p>Recommended For:</p> <p>Sealing surfaces with adhesion problems such as perlite, concrete, plaster, cement, asbestos cement and brick</p> <p>Binding and stabilising tempera, limewash, distemper, whitewash and other unconsolidated coatings</p> <p>Preparing highly absorbent or degraded substrates prior to painting</p> <p>Hidrocril helps ensure a stable, well-sealed surface, improving the performance and durability of subsequent coatings.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <table border="1"> <thead> <tr> <th></th> <th>20 l</th> <th>4 l</th> <th>750 ml</th> </tr> </thead> <tbody> <tr> <td><input checked="" type="checkbox"/> Clear/Transparent (81.006)</td> <td>•</td> <td>•</td> <td>•</td> </tr> </tbody> </table>		20 l	4 l	750 ml	<input checked="" type="checkbox"/> Clear/Transparent (81.006)	•	•	•
	20 l	4 l	750 ml							
<input checked="" type="checkbox"/> Clear/Transparent (81.006)	•	•	•							
<p>AKRIL - 80 Semi-matt</p> 	<p>Solvent-based acrylic sealer concentrate. For interior and exterior use. Cleaning and dilution with white spirit D-16 (Code 50.012). Mixing ratio 1:1 (D-16 / Akрил-80).</p> <p> THE INTERNATIONAL EPD SYSTEM</p> <p><input checked="" type="checkbox"/> Clear (42.115)</p>	<p>Akril-80 evens out surface absorption. Recommended for sealing surfaces and strengthening damaged or absorbent surfaces (plaster, stone, cement, concrete, old paint, etc.).</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <table border="1"> <thead> <tr> <th></th> <th>15 l</th> <th>4 l</th> <th>750 ml</th> </tr> </thead> <tbody> <tr> <td><input checked="" type="checkbox"/> Clear (42.115)</td> <td>•</td> <td>•</td> <td>•</td> </tr> </tbody> </table>		15 l	4 l	750 ml	<input checked="" type="checkbox"/> Clear (42.115)	•	•	•
	15 l	4 l	750 ml							
<input checked="" type="checkbox"/> Clear (42.115)	•	•	•							
<p>PRIMERLITE Matt</p> 	<p>Solvent-based primer based on Pliolite resins. For interior and exterior use. Cleaning and dilution with chlorinated rubber solvent D-40 (Code 50.000).</p> <p> THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (21.702)</p>	<p>Recommended as a primer for cement and concrete surfaces where a permeable system of the highest quality is required. Its resistance to alkalis and high penetration power stand out.</p> <p>Primerlite is the primer of choice for JUNO's Exterior paint systems, and is often prescribed for use with Novokril, Junokril, Bikril, etc.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <table border="1"> <thead> <tr> <th></th> <th>15 l</th> <th>4 l</th> <th>750 ml</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> White (21.702)</td> <td></td> <td>•</td> <td>•</td> </tr> </tbody> </table>		15 l	4 l	750 ml	<input type="checkbox"/> White (21.702)		•	•
	15 l	4 l	750 ml							
<input type="checkbox"/> White (21.702)		•	•							

Hydrophobic treatment

<p>SILOXANE SEALER</p> 	<p>Solvent-based protection for porous mineral surfaces. Formulated with polysiloxane compounds as a hydrophobic impregnation to reduce the absorption of rainwater. Allows water to bead on top of the substrate. For exterior use. Product ready to use, do not dilute. Cleaning with white spirit D-16 (Code 50.012).</p> <p> THE INTERNATIONAL EPD SYSTEM</p> <p><input checked="" type="checkbox"/> Clear (68.104)</p>	<p>Recommended for improving protection against rain on vertical surfaces. Maintains breathability on non-vitrified brick, sandstone, natural stone, concrete and masonry, etc. Forms a long-lasting water-repellent barrier that protects the surface from the elements and won't crack or peel with time. Does not alter the appearance of the treated surface.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <table border="1"> <thead> <tr> <th></th> <th>20 l</th> <th>4 l</th> <th>750 ml</th> </tr> </thead> <tbody> <tr> <td><input checked="" type="checkbox"/> Clear (68.104)</td> <td>•</td> <td>•</td> <td>•</td> </tr> </tbody> </table>		20 l	4 l	750 ml	<input checked="" type="checkbox"/> Clear (68.104)	•	•	•
	20 l	4 l	750 ml							
<input checked="" type="checkbox"/> Clear (68.104)	•	•	•							



WATERPROOFING

Horizontal waterproofing · Façades & vertical waterproofing

Horizontal waterproofing

<p>GOTEPUR Semi-matt</p>  <p>Waterproofing Colour CARD</p>	<p>100% polyurethane elastomeric waterproof membrane.</p> <p>Formulated with 100% polyurethane resins, providing excellent waterproofing and mechanical properties. Provides high resistance to UV rays and strong adhesion to mineral surfaces. Maximum elasticity against cracks up to 1 mm. Effective anti-carbonation barrier. Improves surface energy efficiency levels. Designed for exterior use. Cleaning and dilution with water.</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p>! 15 l</p> <p>White (62.895) Red* (62.894)</p>	<p>Recommended for waterproofing roofs, terraces, and screeds subject to continuous pedestrian traffic.</p> <p>Particularly effective in preventing moisture issues on low-inclination surfaces that require maximum resistance to standing water.</p> <p>Also suitable for substrates with cracks up to 1 mm. Allows for treated surfaces to be tiled.</p> <p><i>APPROVAL CERTIFICATES: TESTS: EPD (Certified with Environmental Product Declaration) - Direct pull-off adhesion - Water vapour permeability - Crack resistance Class A4 - Solar reflectance - Waterproofing - Liquid water transmission.</i></p> <p>ADHESION TO SUBSTRATE WATER VAPOUR PERMEABILITY CRACK RESISTANCE CLASS A4 SOLAR REFLECTANCE</p> <p>WATERPROOFING LIQUID WATER TRANSMISSION RESISTANCE TO STATIC AND DYNAMIC LOADS</p>
<p>JUNOTERAS PUR Semi-matt</p>  <p>Waterproofing Colour CARD</p>	<p>Water-based elastomeric waterproof polyurethane coating.</p> <p>Formulated with acrylic and polyurethane copolymers, with excellent waterproofing and mechanical properties. Perfect adhesion to mineral surfaces. Good resistance to UV rays. High filling capacity for cracks and small fissures up to 0.6 mm. Improves surface energy efficiency levels. Designed for exterior use. Cleaning and dilution with water.</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p>! 15 l 4 l</p> <p>White (62.831) Red* (62.832)</p>	<p>Recommended for waterproofing roofs, terraces, and screeds with cracks up to 0.6 mm, provided there is a water drainage slope of at least 1%.</p> <p>Also particularly suited for moisture control in hard-to-access areas that are not subject to continuous pedestrian traffic (though occasional foot traffic is acceptable) and where low water absorption is required.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Direct pull-off adhesion - Water vapour permeability - Anti-carbonation - Crack resistance Class A3 - Solar reflectance - Waterproofing - Liquid water transmission - Fire-retardant B-s1, d0.</i></p> <p>ADHESION TO SUBSTRATE WATER VAPOUR PERMEABILITY ANTI-CARBONATION CRACK RESISTANCE CLASS A3 SOLAR REFLECTANCE</p> <p>LIQUID WATER TRANSMISSION RESISTANCE TO STATIC AND DYNAMIC LOADS FIRE-RETARDANT B-s1, d0</p>
<p>JUNOTERAS Semi-matt</p>  <p>Waterproofing Colour CARD</p>	<p>Water-based elastomeric waterproof coating.</p> <p>Formulated with acrylic-styrene copolymers. Junoteras provides excellent surface adhesion and opacity. Improves surface energy efficiency. For exterior use. Cleaning and dilution with water.</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p>! 15 l 4 l</p> <p>White (62.641) Green* (62.643) Tile* (62.645) Red* (62.642) Grey* (62.644) Black* (62.654)</p>	<p>Recommended for waterproofing roofs, terraces, and screeds, provided there is a water drainage slope of at least 1% and cracks up to 0.6 mm.</p> <p>Also particularly effective in mitigating moisture issues in hard-to-access areas that are not subject to continuous pedestrian traffic.</p> <p><i>APPROVAL CERTIFICATES: TESTS: EPD (Certified with Environmental Product Declaration) - Direct pull-off adhesion - Water vapour permeability - Anti-carbonation - Liquid water transmission - Solar reflectance - Fire-retardant B-s1, d0.</i></p> <p>ADHESION TO SUBSTRATE WATER VAPOUR PERMEABILITY ANTI-CARBONATION</p> <p>LIQUID WATER TRANSMISSION SOLAR REFLECTANCE FIRE-RETARDANT B-s1, d0</p>

Façades & vertical waterproofing

ELASTIFLEX PLUS

Semi-matt



Certified elastomeric waterproof paint for cracks up to 4 mm, with anti-mould preservatives. Maximum elasticity.

Formulated with photocrosslinkable acrylic resins with anti-carbonation protection and excellent mechanical and waterproofing properties. Wide range of permanent elasticity (from -20°C to 60°C). Improves surface energy efficiency.

For exterior use.

Cleaning and dilution with water.

Recommended for the vertical waterproofing of façades, walls, partition walls, and light wells. Especially suitable for surfaces with cracks ranging from 2 to 4 mm.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Direct pull-off adhesion - Water vapour permeability - Anti-carbonation - Liquid water transmission - Crack resistance Class A5 - Solar reflectance - Fire-retardant B-s1, d0.



15 l



White (62.767)

ELASTIFLEX

Semi-matt



Certified elastomeric waterproof paint for cracks up to 1,5 mm, with anti-mould preservatives. Maximum elasticity.

Formulated with photocrosslinkable acrylic resins with anti-carbonation protection and excellent mechanical and waterproofing properties. Wide range of permanent elasticity (from -20°C to 60°C). Improves surface energy efficiency.

For exterior use.

Recommended for the vertical waterproofing of façades, walls, partition walls, and light wells. Especially suitable for surfaces with cracks ranging from 0,9 to 1,5 mm.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Direct pull-off adhesion - Water vapor permeability - Anti-carbonation - Liquid water transmission - Crack resistance Class A4 - Solar reflectance - Fire-retardant B-s1, d0.



15 l

4 l



White base/P (62.601)

Red* (62.602)



Deep base/TR (62.695)

COVERFIX

Matt



Certified elastomeric waterproof paint for cracks up to 0,2 mm, with anti-mould preservatives.

Formulated with acrylic copolymers and elastomeric resins for withstanding movements in weak and exposed surfaces such as plaster, gypsum, etc.

Great filling power, and good coverage.

Matt crack-bridging finish that conceals joints and splices. For interior use.

Cleaning and dilution with water.

Recommended for the vertical waterproofing of façades, walls, partition walls, and light wells. Especially suitable for surfaces with cracks up to 0,2 mm.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.



15 l

4 l



White (62.875)



INTERIOR

Interior emulsions · Trade emulsions ideal for spraying · Specialist interior paints · AENOR certified washable paints · Interior tinting bases · Sealers · Stain blocks

Interior emulsions

<p>B-12 Matt</p>  	<p>Premium water-based lustre paint with excellent levelling, washability and a silky touch. With anti-mould protection.</p> <p>Premium vinyl copolymer-based paint with broad spectrum of anti-fungal and mould protection. Suitable for all interior walls and ceilings. Cleaning and dilution with water.</p>  <p>White (72.010)</p>	<p>Recommended for decorating plaster, cement or masonry surfaces that require mould protection. Specified and used in high-end decoration jobs for maximum finish and protection. Also recommended for kitchens and bathrooms, or for high-traffic areas such as hallways. Highly wet-rub resistant.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</p>  <p>15 l 4 l 750 ml</p> <p>• • •</p>
<p>B-10 Matt</p>  	<p>Durable water-based paint with a semi-matt lustre finish. With anti-mould protection and non-drip/splatter formulation.</p> <p>B-10 is a high quality vinyl copolymer paint offering excellent coverage, opacity and ease of application. Suitable for all interior walls and ceilings. Cleaning and dilution with water.</p>  <p>White (72.000)</p>	<p>Ideal for high-quality interior decoration of walls and ceilings in any type of building. Washable and stain resistant, perfect for kitchens, children's rooms, hallways, etc.</p> <p>B-10 splashes to a minimum level when applied making it ideal for decorating lived-in spaces.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</p>  <p>15 l 4 l 750 ml</p> <p>• • •</p>
<p>B-7 ECOLOGICAL Matt</p>  	<p>Eco-friendly water-based paint with the highest European environmental certification.</p> <p>Formulated with vinyl copolymers and free from solvents, volatile organic compounds (VOCs) and alkylphenol ethoxylate derivatives. Solvent-free, odourless and emission-free. For interior use. Clean tools and dilute with water.</p>  <p>White (72.195)</p>	<p>Recommended for the decoration of hospitals, nurseries, babies' rooms and accommodation for hypersensitive individuals. Immediate re-occupancy after application. Highly resistant to wet scrubbing.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with an Environmental Product Declaration) - VOC emissions tested in accordance with AgBB 2018 criteria - A⁺ rating - EU Ecolabel (European Ecolabel) - Reaction to fire classification: B-s1,d0 - Washability and opacity: Class 2 in accordance with ISO 13300:2002.</p>       <p>15 l 4 l</p> <p>• •</p>
<p>B-5 Matt</p>  	<p>High-opacity, high-performance water-based emulsion offering excellent coverage and spreading rate. Incorporates anti-mould preservatives and advanced anti-splatter technology for cleaner, easier application.</p> <p>Formulated with durable acrylic copolymers for a smooth, even finish. For interior use. Clean tools with water and dilute as required.</p>  <p>White (73.001)</p>	<p>B-5 dries to a beautiful, smooth matt finish that is fully wipeable and formulated to help conceal surface imperfections. Also ideal for protection against the formation of fungi and mould in kitchens and bathrooms. B-5 is also fire retardant. Wet-rub resistant.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard - Certified Class 2 for Washability and Class 1 for Opacity as per standard UNE-EN 13300-2002.</p>    <p>15 l 10 l 4 l 2,5 l 750 ml</p> <p>• • • • •</p>
<p>B-4 NATURE Matt</p>  	<p>Water-based paint with A⁺ Certification for the highest standard of Indoor Air Quality.</p> <p>Formulated with vinyl copolymers. Classified A⁺, the top rating for Indoor Air Quality, ensuring very low chemical emissions. Solvent-free and odourless. For interior use. Clean tools and dilute with water.</p>  <p>White (73.271)</p>	<p>Recommended for the decoration of hospitals, nurseries, babies' rooms and accommodation for hypersensitive individuals. Immediate re-occupancy after application.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with an Environmental Product Declaration) - A⁺ Certification - Reaction to fire classification: B-s1,d0.</p>   <p>15 l 4 l</p> <p>• •</p>

Trade emulsions ideal for spraying

<p>J-33 Extra-Matt</p>  <p>ANTI-SPLATTER TECHNOLOGY</p>	<p>Premium ultra-matt, anti-reflective water-based paint designed to minimise glare and disguise surface imperfections. Delivers excellent opacity and a smooth, uniform, non-flashing finish.</p> <p>Contains anti-mould preservatives to protect the dried coating against fungal growth.</p> <p>Low-odour, for interior use. Clean tools and dilute with water.</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p>	<p>Recommended for: ceilings and walls in areas exposed to strong natural or artificial light, including living spaces, offices and commercial interiors where reduced glare and visual comfort are essential.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard - Certified Class 1 for Washability and Opacity as per standard UNE-EN 13300-2002.</i></p> <p>Coming soon</p> <table border="1"> <thead> <tr> <th>15 l</th> <th>4 l</th> <th>750ml</th> </tr> </thead> <tbody> <tr> <td>•</td> <td>•</td> <td>•</td> </tr> </tbody> </table> <p>White (73.424)</p>	15 l	4 l	750ml	•	•	•
15 l	4 l	750ml						
•	•	•						
<p>J-28 Extra-matt</p> 	<p>Water-based emulsion paint with an extra-matt finish, special for coating projected plaster and plasterboards. With anti-mould protection.</p> <p>Formulated with acrylic copolymers in aqueous dispersion, titanium dioxide and extenders.</p> <p>Suitable for all interior walls and ceilings.</p> <p>Cleaning and dilution with water.</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p>	<p>Recommended for general use in construction and decoration, especially to hide fillers and joints on applied plaster, plasterboard or gypsum. J-28 is excellent for spraying large surface areas and touches up very well.</p> <p>Resistant to wet rubbing and scuffing.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard - Certified Class 2 for Washability and Opacity as per standard UNE-EN 13300-2002.</i></p> <table border="1"> <thead> <tr> <th>15 l</th> <th>4 l</th> </tr> </thead> <tbody> <tr> <td></td> <td>•</td> </tr> <tr> <td></td> <td>•</td> </tr> </tbody> </table> <p>White (73.168)</p>	15 l	4 l		•		•
15 l	4 l							
	•							
	•							
<p>J-25 Matt</p> 	<p>High-opacity interior emulsion offering superb coverage and built-in anti-mould protection.</p> <p>Formulated with acrylic copolymers in aqueous dispersion, titanium dioxide and selected extenders, it provides a bright, dense white finish with excellent value for money.</p> <p>Suitable for interior walls and ceilings.</p> <p>Clean tools and dilute with water.</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p>	<p>Recommended for professional and trade use across residential and commercial projects, particularly on walls and ceilings where a classic matt finish is specified. Ideal for spray application on new-build residential and commercial properties.</p> <p>Offers good resistance to wet abrasion and everyday scuffing, making it suitable for high-traffic interiors. J-25 also applies effortlessly by spray, ensuring a consistent, uniform finish.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard - Certified Class 2 for Washability and Class 1 for Opacity as per standard UNE-EN 13300-2002.</i></p> <table border="1"> <thead> <tr> <th>15 l</th> <th>4 l</th> </tr> </thead> <tbody> <tr> <td></td> <td>•</td> </tr> <tr> <td></td> <td>•</td> </tr> </tbody> </table> <p>White (73.150)</p> <p>Black* (73.173)</p>	15 l	4 l		•		•
15 l	4 l							
	•							
	•							

Specialist interior paints

<p>ANTI-CONDENSATION Matt</p> 	<p>Water-based special anti-condensation paint. With anti-mould protection.</p> <p>Formulated with acrylic copolymers and glass beads which prevent water condensation and mould growth on its surface.</p> <p>For interior use.</p> <p>Ready to use. Do not dilute.</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p>	<p>Specifically designed to significantly reduce condensation on walls and ceilings in humid environments - by preventing condensation mould will not grow.</p> <p>Ideal for use in bathrooms, kitchens, pantries, north facing rooms with poor insulation, roller shutter boxes, fitted wardrobes, computer rooms, etc. Also ideal for painting cold-water pipes.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Conductivity certificate.</i></p> <table border="1"> <thead> <tr> <th>15 l</th> <th>4 l</th> <th>750 ml</th> </tr> </thead> <tbody> <tr> <td>•</td> <td>•</td> <td>•</td> </tr> </tbody> </table> <p>White (62.650)</p>	15 l	4 l	750 ml	•	•	•
15 l	4 l	750 ml						
•	•	•						

AENOR certified washable paints

<p>N-5 Matt</p> 	<p>Matt water-based emulsion paint with AENOR certification for washability. With anti-mould protection.</p> <p>Based on acrylic copolymers in aqueous dispersion. Resistant to wet rubbing, breathable, with excellent hiding power and maximum performance.</p> <p>For interior use.</p> <p>Cleaning and dilution with water.</p> <p> EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p><input type="checkbox"/> White (73.040)</p>	<p>Recommended for general use in construction and decoration on typical surfaces such as plaster, plasterboard, gypsum, concrete, cement, etc. Ideal for spraying. Recommended for public and private projects where finishes with guaranteed washability and anti-mould protection is required. Ideal for high traffic and frequently used public areas, such as schools, hospitals, kindergardens, prisons, etc.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - AENOR Certified for washability - Fire retardant to B-s1,d0 standard.</i></p> <p> </p> <table border="1"> <thead> <tr> <th></th> <th>15 l</th> <th>4 l</th> <th>750 ml</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> White (73.040)</td> <td>•</td> <td>•</td> <td>•</td> </tr> </tbody> </table>		15 l	4 l	750 ml	<input type="checkbox"/> White (73.040)	•	•	•
	15 l	4 l	750 ml							
<input type="checkbox"/> White (73.040)	•	•	•							
<p>CASTOR-N Matt</p> 	<p>Matt water-based emulsion paint with AENOR certification for washability. With anti-mould protection.</p> <p>Based on acrylic copolymers in aqueous dispersion.</p> <p>For interior use.</p> <p>Cleaning and dilution with water.</p> <p> EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p><input type="checkbox"/> White (73.113)</p>	<p>Recommended for general use in construction and decorating on plaster, plasterboard, concrete, cement surfaces, etc. Ideal for spraying.</p> <p>Great washability, with high hiding power and great performance. Required in public and private projects with a comprehensive system of certified building specifications.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - AENOR - Fire retardant to B-s1,d0 standard.</i></p> <p> </p> <table border="1"> <thead> <tr> <th></th> <th>15 l</th> <th>4 l</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> White (73.113)</td> <td>•</td> <td>•</td> </tr> </tbody> </table>		15 l	4 l	<input type="checkbox"/> White (73.113)	•	•		
	15 l	4 l								
<input type="checkbox"/> White (73.113)	•	•								

Interior tinting bases

<p>JUNOPROF Matt</p>  <p></p> <p> JUNO Combina JUNOMATIC Tinting System</p>	<p>A beautifully refined interior emulsion tinting base, created to deliver exceptional depth and clarity of colour. Its richly pigmented formulation provides outstanding opacity, excellent coverage and a smooth, even finish with impressive durability and washability.</p> <p>Enhanced with anti-mould protection and a low-splatter formulation for effortless application and a flawless result.</p> <p>Crafted with high-quality acrylic copolymers in aqueous dispersion.</p> <p>For interior walls and ceilings.</p> <p>Clean tools with water and dilute as required.</p> <p> EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p><input type="checkbox"/> White base/P (88.750)</p> <p> Medium base/D (88.751)</p> <p> Deep base/TR (88.752)</p> <p> Yellow base/GL* (88.753)  Red base/RD* (88.754)</p>	<p>Low-odour interior emulsion delivering a durable, hard-wearing finish on blockwork, brickwork, cement render, concrete, plaster and plasterboard.</p> <p>Ideal for refined residential interiors as well as hotels, hospitals and public buildings where both performance and appearance are paramount.</p> <p>Available in an extensive colour range, including 300 exclusive new JUNO Designer Palette shades.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with an Environmental Product Declaration) - A+ Certified - Reaction to fire classification: B-s1,d0 - Complies with the AgBB health-related evaluation procedure for VOC emissions in accordance with German assessment criteria - Classified Class 1 for washability and Class 2 for opacity in accordance with EN 13300:2002.</i></p> <p>    </p> <table border="1"> <thead> <tr> <th></th> <th>12 l</th> <th>4 l</th> <th>2,5 l</th> <th>750 ml</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> White base/P (88.750)</td> <td>•</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Medium base/D (88.751)</td> <td>•</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Deep base/TR (88.752)</td> <td>•</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Yellow base/GL* (88.753)  Red base/RD* (88.754)</td> <td>•</td> <td>•</td> <td>•</td> <td>•</td> </tr> </tbody> </table>		12 l	4 l	2,5 l	750 ml	<input type="checkbox"/> White base/P (88.750)	•	•	•	•	 Medium base/D (88.751)	•	•	•	•	 Deep base/TR (88.752)	•	•	•	•	 Yellow base/GL* (88.753)  Red base/RD* (88.754)	•	•	•	•
	12 l	4 l	2,5 l	750 ml																							
<input type="checkbox"/> White base/P (88.750)	•	•	•	•																							
 Medium base/D (88.751)	•	•	•	•																							
 Deep base/TR (88.752)	•	•	•	•																							
 Yellow base/GL* (88.753)  Red base/RD* (88.754)	•	•	•	•																							

Sealers

<p>HIDROCRIL Semi-matt</p> 	<p>Hidrocril – Penetrating Acrylic water-based Sealer & Binding Primer. Concentrated water-based acrylic sealer designed to penetrate, bind and stabilise porous or powdery surfaces. Suitable for interior and exterior use, it provides outstanding adhesion and creates a sound surface for subsequent decoration.</p> <ul style="list-style-type: none"> - Deep-penetrating formula that consolidates porous and friable substrates - Binds chalky, powdery or unstable surfaces - Promotes excellent adhesion for topcoats - Equalises surface porosity for a uniform finish - Water-based – low odour and easy clean-up - Dilutable concentrate (mixing ratio 4:1 – Water: Hidrocril) <p> EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p><input checked="" type="checkbox"/> Clear/Transparent (81.006)</p>	<p>Recommended For:</p> <p>Sealing surfaces with adhesion problems such as perlite, concrete, plaster, cement, asbestos cement and brick</p> <p>Binding and stabilising tempera, limewash, distemper, whitewash and other unconsolidated coatings</p> <p>Preparing highly absorbent or degraded substrates prior to painting</p> <p>Hidrocril helps ensure a stable, well-sealed surface, improving the performance and durability of subsequent coatings.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <p style="text-align: right;">20 l 4 l 750 ml</p> <p style="text-align: right;">• • •</p>
<p>AQUASELL Matt</p> 	<p>Premium water-based sealer specially developed for spray-applied and projected plasters. Formulated with advanced acrylic resins in aqueous dispersion, it offers excellent filling and sealing properties, helping to create a uniform, stable surface prior to decoration.</p> <p>Suitable for interior and exterior use. Clean tools and dilute with water.</p> <p> EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p><input type="checkbox"/> White (21.203)</p>	<p>Recommended as a preparatory base coat on substrates with varying levels of porosity, including mineral backgrounds, plasterboard and applied or projected plasters, ensuring consistent absorption and an even finish.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with an Environmental Product Declaration) - Reaction to fire classification: B-s1,d0.</i></p> <div style="text-align: right; border: 1px solid black; padding: 2px; width: fit-content; margin: 0 auto;"> FIRE-RETARDANT B-s1,d0 </div> <p style="text-align: right;">15 l 4 l</p> <p style="text-align: right;">• •</p>
<p>ANTI-HUMIDITY SEALER Matt</p> 	<p>High-performance, quick-drying anti-damp sealer designed to isolate and block moisture-related staining. Formulated with pliolite resins, Portland cement and specialised insulating additives, it helps prevent the reappearance of damp patches, grease and oily marks. Provides a reliable barrier on walls affected by intermittent moisture.</p> <p>Suitable for interior and exterior use, particularly in kitchens, utility areas, basements and other humidity-prone environments.</p> <p>Clean tools and dilute with white spirit D-16 (Code 50.012).</p> <p> EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p><input type="checkbox"/> White (88.000)</p>	<p>Recommended for treating areas affected by intermittent damp, including ceilings, walls, basements and garages. Its quick-drying formulation allows overcoating with most types of paint, wallpapering, or the application of other suitable decorative finishes.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with an Environmental Product Declaration).</i></p> <p style="text-align: right;">4 l 750 ml</p> <p style="text-align: right;">• •</p>

Stain blocks

<p>STAIN BLOCK Matt</p> 	<p>Synthetic stain block with Plioway. Odourless. Formulated with high quality Plioway resins with stain-resistant and mould prevention properties. Suitable for use on interior walls and ceilings. Cleaning and dilution with odourless solvent D-69 (Code 50.073).</p> <p> THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (21.350)</p>	<p>Recommended for all types of surfaces that have damp, grease, nicotine or other stains, or surfaces that have lost their hue. Also recommended as a finishing coat. When re-coating with water-based emulsions ensure the stain block has fully cured to avoid stains resurfacing. <i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <table border="1" data-bbox="1161 544 1473 611"> <thead> <tr> <th>15 l</th> <th>4 l</th> <th>750 ml</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">•</td> <td style="text-align: center;">•</td> <td style="text-align: center;">•</td> </tr> </tbody> </table>	15 l	4 l	750 ml	•	•	•
15 l	4 l	750 ml						
•	•	•						
<p>JUNOSTOP Matt</p> 	<p>Synthetic stain block with Plioway. Formulated with special resins with stain resistant and mould prevention properties. Suitable for use on interior walls and ceilings. Cleaning and dilution with odourless solvent D-69 (Code 50.073).</p> <p> THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (21.300)</p>	<p>Recommended for all types of surfaces that have damp, grease, nicotine or other stains, or surfaces that have lost their hue. Also recommended as a finishing coat. When re-coating with water-based emulsions ensure the stain block has fully cured to avoid stains resurfacing. <i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <table border="1" data-bbox="1161 887 1473 954"> <thead> <tr> <th>15 l</th> <th>4 l</th> <th>750 ml</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">•</td> <td style="text-align: center;">•</td> <td style="text-align: center;">•</td> </tr> </tbody> </table>	15 l	4 l	750 ml	•	•	•
15 l	4 l	750 ml						
•	•	•						
<p>STAIN BLOCK SPRAY Matt</p> 	<p>High-performance white synthetic stain-blocking spray, designed for fast, effective isolation of stubborn marks. Quick-drying and exceptionally easy to apply, it seals and prevents the bleed-through of water stains, smoke damage, grease and other common contaminants. Suitable for interior and exterior use. 500 ml aerosol for convenient, precise application.</p>	<p>Recommended for covering and permanently blocking all types of stubborn stains, including grease, damp, nicotine and marker pen. Its easy application, rapid drying time and durable finish make it an ideal base coat prior to overpainting with most decorative topcoats.</p> <table border="1" data-bbox="1161 1261 1473 1328"> <thead> <tr> <th>500 ml</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">•</td> </tr> </tbody> </table>	500 ml	•				
500 ml								
•								
<p>AQUATAPA Matt</p> 	<p>Odourless water-based stain block primer. Formulated with acrylic resins with stain resistant properties to seal, bind and prevent the migration of stains through the paint film. For interior walls and ceilings. Cleaning with water. Do not dilute.</p> <p> THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (21.205)</p>	<p>Recommended for stains including smoke damage, nicotine/inks and ideal for areas exposed to smoke, steam or condensation (boilers outlets, tanks, fireplaces). Seals mineral substrates such as powdery surfaces, limewash and distemper. Also recommended as a finishing coat. <i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <table border="1" data-bbox="1161 1648 1473 1715"> <thead> <tr> <th>15 l</th> <th>4 l</th> <th>750 ml</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">•</td> <td style="text-align: center;">•</td> <td style="text-align: center;">•</td> </tr> </tbody> </table> <p style="text-align: right;"></p>	15 l	4 l	750 ml	•	•	•
15 l	4 l	750 ml						
•	•	•						





FLOOR COATINGS

1K Floor coatings · 2K Floor coatings · Microbeads · 100% Solids 2K Epoxy system · Pool/Milking parlour/Traffic Marking · Line marking for grass/turf

1K Floor coatings

JUNOSOL Semi-matt



Easy to apply and quick-dry water-based one component floor paint.

Formulated with styrene-acrylic resins that provide great strength.

For interior and exterior use.

Cleaning and dilution with water.

Suitable for internal and external applications such as on tarmac, concrete, asphalt, walls and bricks. Ideal for painting sports facilities, line marking and car parks with light traffic.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Class 3 anti-slip resistance with special micro-beads (see page 38) - Fire retardant to B-s1,d0 standard.



White (06.162)

Tennis green* (06.150)

Turkish red* (06.160)

Yellow* (06.166)

Cement grey* (06.163)

Light grey* (06.164)

15 l

4 l

• •

• -

- •

FLOOR COATINGS
Colour CARD

DYNAMOL Satin



Quick-drying chlorinated rubber paint with high resistance to acids.

Formulated with chlorinated rubber resins with high resistance to acids and alkalis.

For interior and exterior use.

Cleaning and dilution with chlorinated rubber solvent D-40 (Code 50.000).

Ideally suited for application to brickwork, swimming pool enclosures, pool structures, walls, floors, parkings, sewage tanks, etc. Also suitable for milking parlours, stables, kennels and catteries. Not suitable for painting tar and/or bituminous asphalt surfaces due to bleeding.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Class 3 anti-slip resistance with special micro-beads (see page 38).



RAL 9010 (09.500)

Pearl grey* (09.533)

Yellow* (09.525)

Tennis red* (09.568)

Tennis green* (09.552)

15 l

4 l

750 ml

• • •

• • •

FLOOR COATINGS
Colour CARD

2K Floor coatings - Water-based

DYNAPOK AGUA FLOOR PRIMER / CLEAR TOPCOAT 2/C

Satin



Two-pack water-based floor epoxy primer.

Formulated with epoxy resin in aqueous solution. Excellent substrate penetration and filling capacity.

Also formulated to be used as a clear topcoat.

For interior use.

Cleaning and dilution with water.

As a primer (diluted 30%), suitable for sealing new or consolidated concrete and cementitious surfaces, including commercial areas.

As a finishing coat (diluted 10%), it provides durable protection to concrete surfaces exposed to water, grease, mild acids and diluted alkalis.

Ideal for a wide range of industrial and commercial applications, particularly within the food production and healthcare sectors, thanks to its water-based formulation with no added solvents.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).



15 l

4 l

Clear (07.160)

• •

DYNAPOK AGUA EPOXY

Satin



Two-pack water-based epoxy coating, non-toxic and specially formulated for use in areas with limited ventilation. Particularly suited to commercial, food processing and healthcare environments.

Based on epoxy resins in aqueous solution, it provides excellent chemical resistance and a tough, highly durable finish.

For interior use.

Clean tools and dilute with water.

Ideal where hygiene coating is specified, and essential for interior spaces with reduced access to ventilation, where conventional paints with organic solvents would be toxic.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Meets health related evaluation procedure for emissions of VOC's (German AgBB 2018) - A+ Certified - Non-toxic cert.: Non migration of certain elements EN 71-3:2013+A2:2017 - Class 3 anti-slip resistant with special micro-beads (see page 38) - Fire retardant rating for floors to Bfl-s1 standard.



White base/P (07.132)

Grey* (07.145)

Deep base/TR (07.133)

15 l

4 l

• •

• •

FLOOR COATINGS
Colour CARD

JUNOMATIC Tinting System

AQUAPUR FLOOR COATING

High Satin



Two-component water-based polyurethane coating with low VOC emissions. Especially designed for interiors, garage floors, parking lots, etc.

Formulated with water-based polyurethane resins creating a hard and chemically resistant film withstanding wear and tear. Suitable for both interior and exterior use.

Cleaning and dilution with water.

Recommended as a coating for concrete surfaces in the

general industry or on concrete where it is not possible to completely eliminate moisture from the substrate. Also recommended in enclosed, unventilated spaces and on asphalt products such as tar, bituminous materials, and slurries. Particularly recommended as a sealing and protective coat on 100% solid epoxy flooring systems.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - A+ Certified - Meets health related evaluation procedure for emissions of VOC's (German AgBB 2018) - Fire retardant to B-s1,d0 standard.



4 l

White base/P (8.340)

Deep base/TR (8.341)

•

•



2K Floor coatings - Solvent-based

IMPRIMAX PRIMER

Semi-gloss



Two component solvent-based epoxy primer for non-porous surfaces.

Silane-modified epoxy-polyamide reinforcing primer providing class-leading adhesion on smooth non-porous surfaces, like power-floated concrete and tiles.

For interior use.

Cleaning and dilution with epoxy solvent D-90 (Code 50.010).

Recommended as an epoxy adhesion primer coating on non-porous surfaces for interior epoxy systems.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).



15 l 4 l 1 l

Clear (48.725)

•

•

•

PAVIMYC PRIMER

Gloss



Two-component, solvent-based epoxy primer for porous substrates.

Formulated with epoxy resins. Acts as an adhesion promoter for porous surfaces and diamond-ground or milled substrates to be finished with Pavimyc (07.8...) or Pavimyc HB (07.931). For interior use.

Clean tools and dilute with D90 solvent (Code 50.010).

Recommended for concrete floors in indoor car parks, garages, laboratories, chemical plants, refineries, workshops, and, more generally, all types of new and existing industrial or commercial flooring.

Not suitable for application to surfaces coated with tar and/or bituminous asphalt.

15 l

Clear (48.721)

•

PAVIMYC

Gloss



Two-pack epoxy floor paint with excellent hardness and adhesion properties.

Ensures effective protection against carbonation of concrete. Resistance to acids, alkalis and solvents, and provides erosion protection to concrete pavements exposed to traffic, chemicals, cleaning systems, etc.

For interior use only.

Cleaning and dilution with epoxy solvent D-90 (Code 50.010).

Product widely used on concrete floors in industrial and non-industrial settings. Ideal for indoor car parks, laboratories, chemical and pharmaceutical facilities, mechanical workshops, etc. Not recommended for use on asphalt, tar or bitumen treated surfaces.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Class 3 anti-slip resistant with added special micro-beads (see page 35).



15 l 4 l

English red* (07.812)

Green* (07.814)

Grey* (07.807)

•

•

Microbeads

<p>ANTI-SLIP MICROBEADS</p> 	<p>Anti-slip microbeads for floor coatings. Polypropylene microbeads with average diameter of 180 microns to improve the slip resistance of floor surfaces particularly when wet. Add a 150 gram tub for every 4L of paint, and 4 tubs for every 15 L of paint to achieve certified anti-slip protection.</p>	<p>This product gives the following product range from JUNO Class 3 Anti-slip rating: Dynapok agua Floor Epoxy (07.1...), Dynamol (09.5...), Junosol (06.1...), Pavimyc (07.8...), Junoretano (88.8...), and Junopoxi (88.8...).</p> <p>Add to the paint in the following proportion: 4 L (1 x 150 g) 15 L (1 x 600 g) or (4 x 150 g)</p>
<input type="checkbox"/> White (07250)		<p>600 gr 150 gr</p> <p>• •</p>
<p>MICROBEADS FOR PAVIMYC HB 2/C</p> 	<p>Anti-slip microbeads for epoxy high-build floor coating systems. Polyethylene microbeads with an average diameter of 250 microns suitable for obtaining non-slip properties on wet surfaces.</p>	<p>Recommended as an anti-slip additive to obtain class 3 slip resistance in Pavimyc HB 2/C systems. Add a can of 400 grams for every 20 kg of paint.</p>
<input type="checkbox"/> White (07251)		<p>400 gr</p> <p>•</p>

100% Solids 2K Epoxy system

<p>PAVIMYC HB EPOXY PRIMER <i>High Satin</i></p> 	<p>2K Epoxy Primer 100% solids. Formulated based on modified epoxy resins. Easy application. Impermeable to water and water vapour. Very good adhesion and penetration. Interior use and application. Use D-90 thinner for cleaning (Code 50.010).</p> <p> EPD® <small>THE INTERNATIONAL EPD® SYSTEM</small></p>	<p>Recommended for cementitious and concrete substrates. Forms a robust floor coating system when used in combination with Pavimyc HB 2/C (07.931). Serves as a primer coat for JUNO's PAVIMYC HB floor systems (smooth, anti-slip, multi-layer or self-levelling systems).</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p>
<input checked="" type="checkbox"/> Clear (07915)		<p>20 kg</p> <p>•</p>
<p>PAVIMYC HB <i>Gloss</i></p>  <p></p> <p>JUNOMATIC Tinting System</p>	<p>High-build (100% Solids) pigmented 2K epoxy coating to seal and protect floors. Formulated with 100% solids epoxy resins and pigments achieving high chemical resistance and hardness. Great opacity and coverage level. Allows for an even floor surface with low paint consumption. Facilitates cleaning of any type of surface stains/dirt. For interior use. Use D-90 thinner for cleaning (Code 50.010).</p> <p> EPD® <small>THE INTERNATIONAL EPD® SYSTEM</small></p>	<p>Recommended to protect concrete floors from wear and tear, chemical agents thus expanding their life cycle. Pavimyc HB offers different systems for continuous coatings. (smooth, non-slip, self-levelling, multi-layer) with one and same product. Indicated for garages, workshops, parkings, wineries, warehouses, industrial factories, data centres, etc. Not recommended for use on asphalt, tar or bitumen treated surfaces.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - CE Certified (see below) - Bfl-s1 Euroclass Fire retardant certified - Class 3 Anti-slip rating when used with Pavimyc HB Microbeads (see page 35).</i></p> <p>UNE-EN 1062-6:2003 UNE-EN 1062-3:2008 UNE-EN 13529:2005 UNE-EN ISO 6272-1:2012 UNE-EN ISO 7783:2019 UNE-EN 1542:2000 UNE-EN ISO 5470-1:2017 UNE-EN 13892-2:2003</p> <p>  </p>
<input type="checkbox"/> Deep base/TR (07931)		<p>20 kg</p> <p>•</p>

Pool/Milking parlour/Traffic Marking

<p>JUNOSPORT Satin</p> 	<p>Water-based durable, strong and highly flexible paint for swimming pools. Formulated with pure acrylic resins to resist the destructive effects of swimming pool chemicals. Exclusive use for concrete type swimming pools. For interior and exterior use. Cleaning and dilution with water.</p> <p> EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p> 4 l</p> <p> Blue* (06.105)</p>	<p>Formulated for use over old or new concrete based swimming pools. Applied by brush, roller or spray, displaying excellent adhesion over sound previously painted surfaces. Also recommended as floor coating for other types of sports facilities and car parks with light traffic.</p> <p>Blue colour is correct for marking disability car parking spaces.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</p>
<p>PISCICLOR Satin</p> 	<p>Solvent-based durable, strong and highly flexible paint for swimming pools/milking parlours. Formulated with chlorinated rubber resins with extraordinary resistance to weathering, chemical damage and discolouration. Exclusive use for concrete type swimming pools. For interior and exterior use. Cleaning and dilution with chlorinated rubber solvent D-40 (Code 50.000).</p> <p> EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p> 4 l</p> <p> Blue* (09.180)</p>	<p>Recommended for painting swimming pools and milking parlours, sports facilities and car parks with light traffic. Also recommended as floor coating for other types of sports facilities and car parks with light traffic.</p> <p>Blue colour is correct for marking disability car parking spaces.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</p>
<p>JUNOLINEA Matt</p> 	<p>Water-based line marking paint with high hiding power. Not harmful to natural grass. Formulation based on high quality acrylic copolymers, giving bright white lines. For interior and exterior use.</p>	<p>Junolinea is the ultimate white line marking paint for use on football, rugby, hockey pitches and tennis courts and cricket squares. It is used by top professional clubs and give long lasting brilliant white lines (also used on farms, construction sites, hills/woodland, paths for occasional marking/signposting).</p> <p>10 l</p> <p> White (62.550)</p>



TRIM PAINT

Solvent-based enamels · Water-based enamels · Tinting bases - Decorative · Tinting bases - Industrial · Adhesion & anti-corrosive primers · Wood primers

Solvent-based enamels

<p>JUNOLAC ANTIOXIDANT Gloss</p>  <p>Satin</p>  <p>JUNOLAC ANTI-OX Colour CARD JUNOMATIC Tinting System</p>	<p>Quick-drying, anti-corrosive synthetic self-priming enamel. Ready for direct application to new or previously painted steel and iron, whether bare or coated. This high-gloss enamel offers excellent resistance to weathering and corrosive environments, providing long-lasting protection and an outstanding decorative finish. For large surface areas, the use of D-75 Retarding Thinner (Code 50.107) is recommended to optimise application and finish. Suitable for interior and exterior use. Clean tools and dilute with D-16 Thinner (Code 50.012).</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p>Gloss finish</p> <table border="0"> <tr><td> White (04.860)</td><td> Red* (04.866)</td></tr> <tr><td> Black* (04.861)</td><td> Golden yellow* (04.867)</td></tr> <tr><td> Ochre* (04.862)</td><td> Medium grey* (04.868)</td></tr> <tr><td> Arabia Brown* (04.863)</td><td> Marine blue* (04.869)</td></tr> <tr><td> Txoko brown* (04.864)</td><td> Spring green* (04.870)</td></tr> <tr><td> Bordeaux red* (04.865)</td><td> Pine green* (04.871)</td></tr> </table> <p> White base/P (04.897)</p> <p> Deep base/TR (04.895)</p> <p>Satin finish</p> <table border="0"> <tr><td> White (04.880)</td><td> Red* (04.886)</td></tr> <tr><td> Black* (04.881)</td><td> Golden yellow* (04.887)</td></tr> <tr><td> Ochre* (04.882)</td><td> Medium grey* (04.888)</td></tr> <tr><td> Arabia Brown* (04.883)</td><td> Marine blue* (04.889)</td></tr> <tr><td> Txoko brown* (04.884)</td><td> Spring green* (04.890)</td></tr> <tr><td> Bordeaux red* (04.885)</td><td> Pine green* (04.891)</td></tr> </table> <p> White base/P (04.894)</p> <p> Deep base/TR (04.893)</p>	White (04.860)	Red* (04.866)	Black* (04.861)	Golden yellow* (04.867)	Ochre* (04.862)	Medium grey* (04.868)	Arabia Brown* (04.863)	Marine blue* (04.869)	Txoko brown* (04.864)	Spring green* (04.870)	Bordeaux red* (04.865)	Pine green* (04.871)	White (04.880)	Red* (04.886)	Black* (04.881)	Golden yellow* (04.887)	Ochre* (04.882)	Medium grey* (04.888)	Arabia Brown* (04.883)	Marine blue* (04.889)	Txoko brown* (04.884)	Spring green* (04.890)	Bordeaux red* (04.885)	Pine green* (04.891)	<p>Recommended for iron or steel surfaces where exhaustive preparation of the substrate is not possible (large structures, gates, railings, bridges, etc.). Touch dry and repaintable in 1 hour.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard - Anti-corrosive properties certified according to UNE 48316: 2014.</i></p> <p>EPD® ANTI-CORROSIVE FIRE-RETARDANT B-s1,d0</p> <table border="1"> <thead> <tr> <th></th> <th>4 l</th> <th>750 ml</th> <th>375 ml</th> </tr> </thead> <tbody> <tr> <td>Gloss finish</td> <td></td> <td></td> <td style="text-align: right;">In white and black</td> </tr> <tr> <td> White (04.860)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Black* (04.861)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Ochre* (04.862)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Arabia Brown* (04.863)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Txoko brown* (04.864)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Bordeaux red* (04.865)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Red* (04.866)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Golden yellow* (04.867)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Medium grey* (04.868)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Marine blue* (04.869)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Spring green* (04.870)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Pine green* (04.871)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> White base/P (04.897)</td> <td>•</td> <td>•</td> <td>-</td> </tr> <tr> <td> Deep base/TR (04.895)</td> <td>•</td> <td>•</td> <td>-</td> </tr> <tr> <td>Satin finish</td> <td></td> <td></td> <td style="text-align: right;">In white and black</td> </tr> <tr> <td> White (04.880)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Black* (04.881)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Ochre* (04.882)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Arabia Brown* (04.883)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Txoko brown* (04.884)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Bordeaux red* (04.885)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Red* (04.886)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Golden yellow* (04.887)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Medium grey* (04.888)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Marine blue* (04.889)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Spring green* (04.890)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Pine green* (04.891)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> White base/P (04.894)</td> <td>•</td> <td>•</td> <td>-</td> </tr> <tr> <td> Deep base/TR (04.893)</td> <td>•</td> <td>•</td> <td>-</td> </tr> </tbody> </table>		4 l	750 ml	375 ml	Gloss finish			In white and black	White (04.860)	•	•	•	Black* (04.861)	•	•	•	Ochre* (04.862)	•	•	•	Arabia Brown* (04.863)	•	•	•	Txoko brown* (04.864)	•	•	•	Bordeaux red* (04.865)	•	•	•	Red* (04.866)	•	•	•	Golden yellow* (04.867)	•	•	•	Medium grey* (04.868)	•	•	•	Marine blue* (04.869)	•	•	•	Spring green* (04.870)	•	•	•	Pine green* (04.871)	•	•	•	White base/P (04.897)	•	•	-	Deep base/TR (04.895)	•	•	-	Satin finish			In white and black	White (04.880)	•	•	•	Black* (04.881)	•	•	•	Ochre* (04.882)	•	•	•	Arabia Brown* (04.883)	•	•	•	Txoko brown* (04.884)	•	•	•	Bordeaux red* (04.885)	•	•	•	Red* (04.886)	•	•	•	Golden yellow* (04.887)	•	•	•	Medium grey* (04.888)	•	•	•	Marine blue* (04.889)	•	•	•	Spring green* (04.890)	•	•	•	Pine green* (04.891)	•	•	•	White base/P (04.894)	•	•	-	Deep base/TR (04.893)	•	•	-
White (04.860)	Red* (04.866)																																																																																																																																																					
Black* (04.861)	Golden yellow* (04.867)																																																																																																																																																					
Ochre* (04.862)	Medium grey* (04.868)																																																																																																																																																					
Arabia Brown* (04.863)	Marine blue* (04.869)																																																																																																																																																					
Txoko brown* (04.864)	Spring green* (04.870)																																																																																																																																																					
Bordeaux red* (04.865)	Pine green* (04.871)																																																																																																																																																					
White (04.880)	Red* (04.886)																																																																																																																																																					
Black* (04.881)	Golden yellow* (04.887)																																																																																																																																																					
Ochre* (04.882)	Medium grey* (04.888)																																																																																																																																																					
Arabia Brown* (04.883)	Marine blue* (04.889)																																																																																																																																																					
Txoko brown* (04.884)	Spring green* (04.890)																																																																																																																																																					
Bordeaux red* (04.885)	Pine green* (04.891)																																																																																																																																																					
	4 l	750 ml	375 ml																																																																																																																																																			
Gloss finish			In white and black																																																																																																																																																			
White (04.860)	•	•	•																																																																																																																																																			
Black* (04.861)	•	•	•																																																																																																																																																			
Ochre* (04.862)	•	•	•																																																																																																																																																			
Arabia Brown* (04.863)	•	•	•																																																																																																																																																			
Txoko brown* (04.864)	•	•	•																																																																																																																																																			
Bordeaux red* (04.865)	•	•	•																																																																																																																																																			
Red* (04.866)	•	•	•																																																																																																																																																			
Golden yellow* (04.867)	•	•	•																																																																																																																																																			
Medium grey* (04.868)	•	•	•																																																																																																																																																			
Marine blue* (04.869)	•	•	•																																																																																																																																																			
Spring green* (04.870)	•	•	•																																																																																																																																																			
Pine green* (04.871)	•	•	•																																																																																																																																																			
White base/P (04.897)	•	•	-																																																																																																																																																			
Deep base/TR (04.895)	•	•	-																																																																																																																																																			
Satin finish			In white and black																																																																																																																																																			
White (04.880)	•	•	•																																																																																																																																																			
Black* (04.881)	•	•	•																																																																																																																																																			
Ochre* (04.882)	•	•	•																																																																																																																																																			
Arabia Brown* (04.883)	•	•	•																																																																																																																																																			
Txoko brown* (04.884)	•	•	•																																																																																																																																																			
Bordeaux red* (04.885)	•	•	•																																																																																																																																																			
Red* (04.886)	•	•	•																																																																																																																																																			
Golden yellow* (04.887)	•	•	•																																																																																																																																																			
Medium grey* (04.888)	•	•	•																																																																																																																																																			
Marine blue* (04.889)	•	•	•																																																																																																																																																			
Spring green* (04.890)	•	•	•																																																																																																																																																			
Pine green* (04.891)	•	•	•																																																																																																																																																			
White base/P (04.894)	•	•	-																																																																																																																																																			
Deep base/TR (04.893)	•	•	-																																																																																																																																																			
<p>JUNOLAC Gloss</p>  <p>Satin / Matt</p> 	<p>High-solids synthetic enamel with outstanding durability. Premium-quality, high-solids, solvent-based alkyd formulation offering excellent flow and levelling, delivering a tough, long-lasting high-gloss finish with superior gloss retention and resistance to wear. Suitable for interior and exterior surfaces (available in gloss and satin finishes). Clean tools and dilute with D-16 Thinner (Code 50.012).</p> <p>EPD® THE INTERNATIONAL EPD® SYSTEM</p> <p>Gloss finish</p> <table border="0"> <tr><td> White (15.000)</td><td> Black* (15.001)</td></tr> </table> <p>Satin finish</p> <table border="0"> <tr><td> White (15.100)</td><td> Black* (15.101)</td></tr> </table> <p>Matt finish</p> <table border="0"> <tr><td> White (15.200)</td><td> Black* (15.201)</td></tr> </table>	White (15.000)	Black* (15.001)	White (15.100)	Black* (15.101)	White (15.200)	Black* (15.201)	<p>Recommended for interior and exterior application on wood and metal surfaces such as doors, window frames, trim and furniture, providing enhanced protection together with a refined, professional finish. Apply in thin, even coats to ensure optimal drying and full curing performance.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Meets health related evaluation procedure for emissions of VOCs AgBB 2018 - A+ Certified - Fire retardant to B-s1,d0 standard.</i></p> <p>AgBB A+ FIRE-RETARDANT B-s1,d0</p> <table border="1"> <thead> <tr> <th></th> <th>4 l</th> <th>750 ml</th> <th>375 ml</th> </tr> </thead> <tbody> <tr> <td>Gloss finish</td> <td></td> <td></td> <td></td> </tr> <tr> <td> White (15.000)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Black* (15.001)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td>Satin finish</td> <td></td> <td></td> <td></td> </tr> <tr> <td> White (15.100)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Black* (15.101)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td>Matt finish</td> <td></td> <td></td> <td></td> </tr> <tr> <td> White (15.200)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td> Black* (15.201)</td> <td>•</td> <td>•</td> <td>•</td> </tr> </tbody> </table>		4 l	750 ml	375 ml	Gloss finish				White (15.000)	•	•	•	Black* (15.001)	•	•	•	Satin finish				White (15.100)	•	•	•	Black* (15.101)	•	•	•	Matt finish				White (15.200)	•	•	•	Black* (15.201)	•	•	•																																																																																																						
White (15.000)	Black* (15.001)																																																																																																																																																					
White (15.100)	Black* (15.101)																																																																																																																																																					
White (15.200)	Black* (15.201)																																																																																																																																																					
	4 l	750 ml	375 ml																																																																																																																																																			
Gloss finish																																																																																																																																																						
White (15.000)	•	•	•																																																																																																																																																			
Black* (15.001)	•	•	•																																																																																																																																																			
Satin finish																																																																																																																																																						
White (15.100)	•	•	•																																																																																																																																																			
Black* (15.101)	•	•	•																																																																																																																																																			
Matt finish																																																																																																																																																						
White (15.200)	•	•	•																																																																																																																																																			
Black* (15.201)	•	•	•																																																																																																																																																			

JUNOPLUS

Gloss



Satin



Matt



JUNOPLUS Colour CARD
JUNOMATIC Tinting System

Synthetic alkyd-based enamel with wide range of colours.

Formulated with alkyd resins.

For use on interior and exterior surfaces (matt finish for interior use only).

Cleaning and dilution with D-16 thinner (Code 50.012).



Recommended for primed wood and metal surfaces. Can also be used on furniture.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.



Gloss finish		4 l	750 ml	375 ml
White (16.000)	Carriage green* (16.011)	•	•	•
Black* (16.001)	Fire red* / RAL 2002 (16.012)			
Chamois* (16.002)	Wagon red* / RAL 3005 (16.021)			
Meadow* (16.003)	Blood red* / RAL 3000 (16.022)			
Grass green* (16.004)	Medium yellow* / RAL 1028 (16.029)			
Ivory* (16.005)	Light grey* / RAL 7035 (16.031)			
Traffic grey* (16.006)	Cloud grey* / RAL 7001 (16.038)			
Ochre* (16.007)	Dark grey* / RAL 7031 (16.039)			
Blue* / RAL 5012 (16.008)	Meadow green* / RAL 6001 (16.054)			
Ultramarine / RAL 5002 (16.009)	Moss green* / RAL 6005 (16.058)			
Bright blue* / RAL 5017 (16.010)	Arabia Brown* (16.069)			

Colours on demand (RAL colour chart, available from the Junomatic system, parting from colours in the Junoplus chart as bases)

Satin finish		4 l	750 ml	375 ml
White (16.100)	Black* (16.101)	•	•	•
Ultramarine* / RAL 5002 (16.109)	Light grey* / RAL 7035 (16.131)			
Wagon red* / RAL 3005 (16.121)	Meadow green* / RAL 6001 (16.154)			
Blood red* / RAL 3000 (16.122)	Moss green* / RAL 6005 (16.158)			
Medium yellow* / RAL 1028 (16.129)	Arabia Brown* (16.169)			

Colours on demand (RAL colour chart, available from the Junomatic system, parting from colours in the Junoplus chart as bases)

Matt finish (for interior use only)		4 l	750 ml	375 ml
White (16.200)	Black* (16.201)	•	•	-

OXIFORJA

Forja



OXIFORJA Colour CARD

Synthetic enamel with a unique forged iron metallic finish effect and antioxidant properties.

Formulated with alkyd resins and additives with a high resistance to weathering.

For interior and exterior use.

Cleaning and dilution with white spirit D-16 (Code 50.012).



Recommended for the protection and decoration of lamp posts, mail boxes, manhole covers, iron gates, metal structures, fences, urban furniture, etc.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).

		4 l	750 ml
Black* (05.700)	Base / Steel grey* (05.701)	•	•
Intense black	Azure	•	•
	Bronze green		
	Gold		
	Oxide red		

(Colours obtained using the Junomatic Tintometric System)

Water-based enamels

WATERPLUS

Satin / Matt



Single-pack water-based Polyurethane enamel paint. Impeccable lacquered finish for walls, furniture and trims.

Water-based multi-surface polyurethane enamel with excellent hardness washability and chemical resistance. Offers excellent application/levelling properties and opacity for an impeccable finish. Resists rubbing, scratches, impacts and most cleaning products.

For interior use.

Cleaning and thinning with water.

Recommended for all types of surfaces, especially wood and metal carpentry. Ideal for painting furniture, kitchens, doors, window trims, skirting boards, etc. and for perfect smooth and resistant finishes on walls, sandwich panels etc.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Meets health related evaluation procedure for emissions of VOCs AgBB 2018 - A+ Certified.



	15 l	4 l	750 ml
Satin finish			
<input type="checkbox"/> White base/P (10.635)	•	•	•
Deep base/TR (10.637)	-	•	•
Matt finish			
<input type="checkbox"/> White base/P (10.640)	•	•	•
Deep base/TR (10.642)	-	•	•



JUNOMATIC Tinting System

AQUALAC

Gloss / Satin / Matt



Water-based multi-surface enamel, with low odour and easy-application properties.

Formulated with quick drying pure acrylic weather resistant resins. Low-odour and extraordinary weather resistance.

For interior and exterior use (gloss and satin finishes). Cleaning and dilution with water.

Recommended for the protection and decoration of properly prepared and primed metal, wood, masonry, plaster/drywall, trims, etc.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Meets health related evaluation procedure for emissions of VOCs AgBB 2018 - A+ Certified - Fire retardant to B-s1,d0 standard.



	4 l	750 ml
Acabado brillante		
<input type="checkbox"/> White base/P (10.300)	•	•
Medium base/D (10.302)	•	•
Deep base/TR (10.303)	•	•
Yellow base/GL* (10.304)	•	•
Red base/RD* (10.305)	•	•
Satin finish		
<input type="checkbox"/> White base/P (10.400)	•	•
Medium base/D (10.402)	•	•
Deep base/TR (10.403)	•	•
Yellow base/GL* (10.404)	•	•
Red base/RD* (10.405)	•	•
Matt finish (for interior use only)		
<input type="checkbox"/> White base/P (10.500)	•	•
Medium base/D (10.502)	•	•
Deep base/TR (10.503)	•	•



AQUALAC Colour CARD

JUNOMATIC Tinting System

TILE PAINT

Satin



Water-based self-priming enamel for tiles. (No primer required). Ideal for ceramic, stone and glass tiles.

Formulated with resins that provide excellent hardness and high resistance to rubbing, scratches, neutral cleaning products, etc.

Immaculate fine and smooth finish.

Excellent adhesion and opacity.

Outstanding resistance and hardness.

Washable and waterproof.

Low odour.

Quick drying.

For indoor use.

Recommended for painting tiles in both bathrooms and kitchens due to its excellent hardness and resistance to neutral cleaning products. Withstands repeated water splash and highly humid environments.

Not recommended for continuous contact with water.



750 ml

<input type="checkbox"/> White (10.850)	•
---	---



Tinting bases - Decorative

JUNOMALTE
Gloss / Satin




JUNOMATIC Tinting System

Synthetic enamel for Junomatic tinting system. Wide range of colours.
For interior and exterior use (exterior: Gloss finish only).
Cleaning and dilution with D-16 white spirit (Code 50.012).

EPD®
THE INTERNATIONAL EPD® SYSTEM

Especially recommended for primed interior and exterior wood and metal surfaces, where it provides a resilient, high-quality finish with enhanced protection against wear and environmental exposure.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).

		4 l	750 ml
Gloss finish			
<input type="checkbox"/> White base/P (88.990)	Medium base/D (88.991)	Deep base/TR (88.992)	• •
Satin finish			
<input type="checkbox"/> White base/P (88.993)	Medium base/D (88.994)	Deep base/TR (88.995)	• •

Tinting bases - Industrial

JUNORAPID S/R
Gloss



JUNOMATIC Tinting System

Quick-drying synthetic enamel for Junomatic industrial tinting system.
For interior and exterior use.
Cleaning and dilution with quick-dry thinner D-17 (Code 50.004).

EPD®
THE INTERNATIONAL EPD® SYSTEM

Ideal and recommended for refinishing or applying to metal surfaces such as automated installations, structures, OEM coatings to forklifts, trucks, tractors, trailers, etc. that require a quick drying enamel.

Application recommended by spraying.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard - Certified for JUNO's protective anti-corrosive systems as per ISO 12944.

		15 l	4 l	750 ml
Gloss finish				
<input type="checkbox"/> White base/P (88.884)	Deep base/TR (88.885)	•	•	•

JUNOPOXI 2/C
Gloss



JUNOMATIC Tinting System

2-component epoxy enamel for Junomatic industrial tinting system. High chemical resistance.
A high quality tintable epoxy for interior and industrial use. This product provides great coverage and is easy to apply. Anti-dust function.
Cleaning and dilution with epoxy solvent D-90 (Code 50.010).

EPD®
THE INTERNATIONAL EPD® SYSTEM

Recommended for protecting metal, cement or concrete surfaces in industrial or marine environments.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Class 3 anti-slip resistance when adding microbeads (see page 38).

		15 l	4 l	1 l
Gloss finish				
<input type="checkbox"/> White base/P (88.882)	Deep base/TR (88.883)	•	•	•

JUNORETANO 2/C
Gloss / Satin / Matt



JUNOMATIC Tinting System

2K multi-surface polyurethane coating for Junomatic industrial tinting system. Great weather resistance. Anti-corrosion certified system.
Suitable for interior and exterior use.
Cleaning and dilution with Junoretano solvent D-70 (Code 50.007).

EPD®
THE INTERNATIONAL EPD® SYSTEM

Recommended for effective protection of all types of surfaces exposed to aggressive atmospheres (metals, concrete, wood, polyester, PVC, etc.).

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Slip resistance of up to Class 3 by adding microbeads (see page 35) - Fire Retardant B-s1,d0 - Certified for JUNO Anticorrosive Systems with UNE EN ISO 12944.

		15 l	4 l	1 l
Gloss finish				
<input type="checkbox"/> White base/P (88.880)	Deep base/TR (88.881)	•	•	•
Satin finish				
<input type="checkbox"/> White base/P (88.872)	Deep base/TR (88.873)	•	•	•
Matt finish				
<input type="checkbox"/> White base/P (88.801)	Deep base/TR (88.802)	•	•	•

Adhesion & anti-corrosive primers

<p>METALEX Matt</p> 	<p>Anti-corrosive zinc-phosphate primer. Formulated with zinc phosphate and alkyd resins with rust inhibiting properties. For interior and exterior use. Cleaning and dilution with white spirit D-16 (Code 50.012).</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (27.000)</p>	<p>Recommended for protecting metal surfaces that require protection against corrosion (except galvanized and aluminium surfaces).</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</p> <p>4 l 750 ml</p> <p>• •</p>
<p>MULTI-SUPPORT Matt</p>  <p></p>	<p>All-purpose synthetic multi-surface adhesion primer. Premium quality quick drying multi-surface primer based on modified alkyd resins and zinc phosphate acting as anti-rust pigment for long term protection. For interior and exterior use. Cleaning and dilution with quick-drying solvent D-17 (Code 50.004).</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p> FIRE RETARDANT B-s1, d0</p> <p> C3</p> <p><input type="checkbox"/> White (27.040) <input type="checkbox"/> Black* (27.045)</p> <p> Deep base/TR (27.055)</p>	<p>This multipurpose bonding primer can be used as an impregnating and adhesion promoting primer for ferrous and non-ferrous metals, such as steel, aluminium, galvanized surfaces, PVC, glass, tiles and different wood materials (interior use only).</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard (white only) - Certified for JUNO's protective anti-corrosive systems as per ISO 12944.</p> <p>15 l 4 l 750 ml</p> <p>• • •</p> <p>- • •</p>
<p>WORKSHOP PRIMER Matt</p> 	<p>Quick-drying synthetic primer. A very quick drying synthetic primer formulated with iron oxides and alkyd resins. For interior and exterior use. Cleaning and dilution with white spirit D-16 (Code 50.012).</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> Oxide red* (22.110) <input type="checkbox"/> Grey* (22.111)</p>	<p>Recommended for preparing iron surfaces both as a workshop primer for temporary protection and as a general purpose primer in fast drying alkyd-based systems for protection in mild to medium atmospheric corrosive environments.</p> <p>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</p> <p>15 l 4 l 750 ml</p> <p>• • •</p>
<p>WATERPRIM Matt</p>  	<p>Multi-surface water-based anti-corrosive adhesion primer. Formulated with high-performance acrylic copolymers and durable anti-corrosive pigments, providing long-lasting protection against rust and oxidation. Its advanced technology delivers effective anti-corrosive performance while maintaining low VOC content and a fast drying time for efficient application. Suitable for interior and exterior use. Clean tools and dilute with water.</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (30.006)</p>	<p>Waterprim delivers outstanding adhesion to a wide range of difficult-to-coat interior and exterior substrates, including glossy surfaces, ceramic tiles, non-ferrous metals (such as aluminium, stainless steel and galvanised steel), vinyl, GRP, uPVC, interior wood, masonry and many other challenging surfaces.</p> <p>APPROVAL CERTIFICATES: Meets health related evaluation procedure for emissions of AgBB 2018 - A+ Certified - Fire retardant to B-s1,d0 standard.</p> <p> FIRE RETARDANT B-s1, d0</p> <p> AgBB</p> <p> A+</p> <p>4 l 750 ml</p> <p>• •</p>

Wood primers

<p>HANGERS Matt</p> 	<p>High-opacity synthetic wood primer and undercoat. A quick-drying primer and undercoat for most new or bare interior and exterior wood surfaces. Provides excellent adhesion and helps to even out variable absorption, creating a smooth, uniform surface for the finishing system. Suitable for interior and exterior use.</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (21.000)</p>	<p>Cleaning and dilution with white spirit D-16 (Code 50.012).</p> <p>Recommended for preparing wooden and masonry surfaces. Can also be used as finishing coats on interior surfaces. Ideal for softwood, plywood, chipboard flake board, MDF, etc.</p> <p>4 l 750 ml</p> <p>• •</p>
<p>NATURESELL Matt</p>  	<p>Quick dry water-based wood primer/undercoat. Naturesell is a water-based, high opacity, dual purpose primer undercoat for interior and exterior woodwork. Formulated with acrylic resins in aqueous dispersion with great resistance and high opacity. For interior and exterior use.</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (21.100)</p>	<p>Cleaning and dilution with water. Ideal for use as a primer for softwoods, hardwoods, chipboard and fibre board.</p> <p>4 l 750 ml</p> <p>• •</p>



WOOD COATINGS

Undercoats and preparation · Water-based varnishes · Solvent-based varnishes

Undercoats & preparation

New
EGURRA PROTECT



Water-based anti-woodworm and fungicidal primer. Preventive.

Formulated with fungicidal and insecticidal additives in emulsion. Propiconazole-free.

For interior and exterior use.
Cleaning and dilution with water.

Recommended for the preventive treatment of wood against blue-stain fungi, large woodworm, termites, and wood-decay fungi.
Suitable for interior and exterior softwood and hardwood.
Suitable for Use Classes 2 and 3 in accordance with EN 335.

Clear (82.500)

2,5 l 750 ml

• •

AQUA BASE
Matt



Clear water-based wood preservative/undercoat for interior wood.

Formulated with acrylic resins.
For interior use.
Cleaning and dilution with water.

Recommended as a sandable undercoat for all kinds of joinery including doors, windows and frames, parquet and other wood surfaces.

Good filling power, easy application, quick drying and odourless. Valid treatment for both water based and synthetic topcoats.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).



Clear (82.414)

4 l 750 ml

• •

Water-based varnishes

AQUA VARNISH
Gloss



Special odourless water-based polyurethane varnish for parquet.

Formulated with single component aliphatic polyurethane resins, providing a non-yellowing film with a high chemical resistance to wear.

For interior use.
Cleaning with water.

Recommended for all types of parquet and wood surfaces due to its ease of application. Quick drying, with high resistance to abrasion and easy cleaning. Preparation is recommended with **Aqua Base** undercoat (Code 82.414).

Product not suitable for oak or chestnut wood due to darkening of the surface treated.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).



Clear (82.410)

4 l 750 ml

• •

AQUADUR VARNISH
Gloss / Satin / Matt



Special water-based acrylic varnish for carpentry. Great hardness and chemical resistance.

Formulated with acrylic resins, which provide a pleasant non-yellowing film.

For interior use.
Cleaning with water.

Recommended for any interior wood surfaces, especially furniture. Recommended primer: **Aqua Base** undercoat (Code 82.414). Product not suitable for oak or chestnut wood due to darkening of the surface treated.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Meets health related evaluation procedure for emissions of AgBB 2018 - A+ Certified - Fire retardant to C-s1,d0 standard.



Clear / Gloss (82.480)

Clear / Satin (82.481)

Clear / Matt (82.482)



4 l 750 ml

• •

• •

• •

LASUR ACUOSO
Satin



Water-based woodstain with water-repellent properties. OPEN PORE protector with UV filters and anti-fungicidal protection.

Formulated with acrylic resins, transparent pigments and fungicidal preservatives, which form a breathable, microporous, elastic, UV resistant film allowing moisture and air to be released.

For interior and exterior use (clear woodstain for interior use only).

Cleaning and dilution with water.

Recommended for wooden surfaces exposed to weathering (wooden trim, doors, window frames, gates, fences, etc.). Does not crack or chip. Allows maintenance coats to be applied directly on to previous coats without need for removal. For interior use.

For undercoat it is recommended to use **Aqua Base** (Code 82.414).

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).



Clear (82.451)

Chestnut* (82.460)

Oregon pine* (82.461)

Oak* (82.462)

Rustic oak* (82.463)

Walnut* (82.464)

Mahogany* (82.465)

Rosewood* (82.466)

Teak* (82.467)

Iroko* (82.468)

4 l 750 ml

• •

LASUR Colour CARD

Solvent-based varnishes

<p>JUNODUR VARNISH Gloss / Satin</p> 	<p>Special synthetic polyurethane varnish for parquet. Hardness and resistance to domestic use. Formulated with urethane resins to obtain a protective, decorative finish, which is pleasant to the touch. For interior use. Cleaning and dilution with white spirit D-16 (Code 50.012).</p> <p>EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> Clear / Gloss (44.001)</p> <p><input type="checkbox"/> Clear / Satin (44.002)</p>	<p>Recommended for restoring and varnishing parquet and wooden floors that require a hard surface which is resistant to domestic use and neutral cleaning products. <i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <table border="1"> <thead> <tr> <th></th> <th>4 l</th> <th>750 ml</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> Clear / Gloss (44.001)</td> <td>•</td> <td>•</td> </tr> <tr> <td><input type="checkbox"/> Clear / Satin (44.002)</td> <td>•</td> <td>•</td> </tr> </tbody> </table>		4 l	750 ml	<input type="checkbox"/> Clear / Gloss (44.001)	•	•	<input type="checkbox"/> Clear / Satin (44.002)	•	•							
	4 l	750 ml																
<input type="checkbox"/> Clear / Gloss (44.001)	•	•																
<input type="checkbox"/> Clear / Satin (44.002)	•	•																
<p>JUNOLAC VARNISH Gloss / Satin / Matt</p> 	<p>Synthetic clear varnish with UV filters. Highlights wood's natural tones. Formulated with alkyd resins and ultraviolet filters for a protective and decorative finish. For interior use. Gloss finish also for exterior use. Cleaning and dilution with white spirit D-16 (Code 50.012).</p> <p>EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> Clear / Gloss (42.037)</p> <p><input type="checkbox"/> Clear / Satin (42.038)</p> <p><input type="checkbox"/> Clear / Matt (42.039)</p>	<p>Recommended for decorating and protecting wood surfaces such as window frames, doors, trim, furniture, etc. <i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <table border="1"> <thead> <tr> <th></th> <th>4 l</th> <th>750 ml</th> <th>375 ml</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> Clear / Gloss (42.037)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td><input type="checkbox"/> Clear / Satin (42.038)</td> <td>•</td> <td>•</td> <td>•</td> </tr> <tr> <td><input type="checkbox"/> Clear / Matt (42.039)</td> <td>•</td> <td>•</td> <td>•</td> </tr> </tbody> </table>		4 l	750 ml	375 ml	<input type="checkbox"/> Clear / Gloss (42.037)	•	•	•	<input type="checkbox"/> Clear / Satin (42.038)	•	•	•	<input type="checkbox"/> Clear / Matt (42.039)	•	•	•
	4 l	750 ml	375 ml															
<input type="checkbox"/> Clear / Gloss (42.037)	•	•	•															
<input type="checkbox"/> Clear / Satin (42.038)	•	•	•															
<input type="checkbox"/> Clear / Matt (42.039)	•	•	•															
<p>JUNOTINTE VARNISH Gloss</p>  <p>JUNOTINTE Colour CARD</p> 	<p>Synthetic coloured varnish with UV filters. For colourful and decorative finish. Formulated with alkyd resins and ultraviolet filters for a protective and decorative finish. For interior and exterior use. Cleaning and dilution with white spirit D-16 (Code 50.012).</p> <p>EPD® THE INTERNATIONAL EPD SYSTEM</p> <p>! </p> <p> <input type="checkbox"/> Pine* (42.040) <input type="checkbox"/> Chestnut* (42.043) <input type="checkbox"/> Walnut* (42.041) <input type="checkbox"/> Teak* (42.044) <input type="checkbox"/> Mahogany* (42.042) <input type="checkbox"/> Rosewood* (42.045) <input type="checkbox"/> <input type="checkbox"/> Oak* (42.046) </p>	<p>Recommended for decorating and protecting wood surfaces such as window frames, doors, trim, furniture, etc <i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <table border="1"> <thead> <tr> <th></th> <th>750 ml</th> <th>375 ml</th> </tr> </thead> <tbody> <tr> <td>! </td> <td>•</td> <td>•</td> </tr> </tbody> </table>		750 ml	375 ml	!	•	•										
	750 ml	375 ml																
!	•	•																
<p>YACHT VARNISH Gloss</p> 	<p>Synthetic high build full gloss varnish with UV filters. Special for harsh weather conditions. Formulated with alkyd resins of great flexibility and ultraviolet filters for a protective, decorative and highly durable finish of the highest quality. For interior and exterior use. Cleaning and dilution with white spirit D-16 (Code 50.012).</p> <p>EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> Clear (42.036)</p>	<p>Recommended and suitable for hard and softwood subjected to harsh weather conditions humidity, salinity and solar exposure. Contains UV filters which protect against strong sunlight. <i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).</i></p> <table border="1"> <thead> <tr> <th></th> <th>4 l</th> <th>750 ml</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> Clear (42.036)</td> <td>•</td> <td>•</td> </tr> </tbody> </table>		4 l	750 ml	<input type="checkbox"/> Clear (42.036)	•	•										
	4 l	750 ml																
<input type="checkbox"/> Clear (42.036)	•	•																



SUNDRIES

Fillers & caulk · Colourants, paint stripper, additives, etc · Thinners & cleaners
· Colour charts & fan decks

Fillers & caulk

<p>JUNO FILLER <i>For preparation work</i></p> 	<p>Shrink & crack resistant filler for interior repairs. Removes small imperfections, grooves, cracks, etc. Theoretical performance: 1 m²/kg/mm thickness. Max. thickness per layer: 5 mm.</p>	<p>White powder. For interior use. Smooth finish.</p>
<p><input type="checkbox"/> White (77.000)</p>		<p>15 kg 5 kg 1 kg</p>
<p>READY MIX FILLER <i>For repairs</i></p> 	<p>Tintable ready mix repair filler. Smooth ready to use finish filler with excellent adhesion. Theoretical performance: 1.75 kg/m²/mm thickness. Max. thickness per layer: 2 mm.</p>	<p>Ready mix filler that can be coloured using JUNO universal colourants (max. 3%). For interior use. Smooth, very fine finish.</p>
<p><input type="checkbox"/> White (77.200)</p>		<p>5 kg 1 kg 500 gr.</p>
<p>SMOOTH FINISH FILLER <i>For finishing</i></p> 	<p>High performance interior finishing filler. For smoothing and levelling walls before painting or wallpapering. Theoretical performance: 1 m²/kg/mm thickness. Max. thickness per layer: 2 mm.</p>	<p>White powder. For interior use. Smooth finish.</p>
<p><input type="checkbox"/> White (77.030)</p>		<p>15 kg</p>
<p>SANDABLE FILLER <i>For renovations</i></p> 	<p>Easy-to-sand interior renovation filler Formulated to mix into a smooth consistency for easy application. Theoretical performance: 0.950 kg/m²/mm thickness. Max. thickness per layer: 5 mm.</p>	<p>White, easy-to-sand powder filler. For interior use. Smooth finish.</p>
<p><input type="checkbox"/> White (77.410)</p>		<p>15 kg</p>
<p>COVER ALL FILLER <i>For renovations</i></p> 	<p>Skimcoat filler for renovations. Smooths and levels textured decorative surfaces. Theoretical performance: 1 m²/kg/mm thickness. Max. thickness per layer: 5 mm.</p>	<p>White powder with good adhesion. For interior use. Smooth finish.</p>
<p><input type="checkbox"/> White (77.406)</p>		<p>15 kg</p>
<p>RAPID FILLER <i>For repairs</i></p> 	<p>A quick-set cement filler for repairs. A high performance quick drying filler for repairs of any masonry surfaces. For skimming surfaces in fine layers, up to 6 mm. Theoretical performance: 1.5 kg/m²/mm thickness. Max. thickness per layer: 5 mm.</p>	<p>White powder. For interior/exterior use. Fine and very hard finish.</p>
<p><input type="checkbox"/> White (77.301)</p>		<p>15 kg 5 kg</p>
<p>QUICK DRYING REPAIR MORTAR <i>For repairs</i></p> 	<p>White powder cement mortar specially designed for repairing, filling and rendering exterior surfaces. Quick set, great filling capacity and excellent adhesion. Easy application. Max. thickness/coat: 5 mm for wall; For repairs no thickness limit.</p>	<p>Practical coverage: 1,23 Kg/m² White powder. Exterior use.</p>
<p><input type="checkbox"/> White (77.305)</p>		<p>15 kg</p>

<p>MULTI-PURPOSE FILLER <i>Repair</i></p> 	<p>Powdered mortar for repairing, rebuilding or joining any surface. Suitable for humid environments such as bathrooms, kitchens, etc. Joins materials of different nature and/or absorption level. Direct application on ceramics. Theoretical performance: 1 kg/m²/mm. Thickness per layer: any thickness.</p>	<p>White powder. For interior/exterior use. Quick-drying.</p>	5 kg	1 kg
<input type="checkbox"/> White (77.050)				
<p>FIBRE enriched FILLER <i>For reinforcement</i></p> 	<p>Ready to use, flexible, fibre reinforced exterior/interior filler. For sealing and reinforcing dynamic cracks and fissures on plaster, concrete, etc. Does not crack or split, has high adhesion and permanent elasticity. Can be painted on, except with solvent based 2-component products. Theoretical performance: 1,2 kg/m²/mm.</p>	<p>Recommended thickness per layer: 0.3 to 3 mm. Light grey paste. For interior/exterior use.</p>	4 l	750 ml
<input type="checkbox"/> Light grey (77.250)				
<p>ANTI-CONDENSATION FILLER <i>Thermal insulation</i></p> 	<p>Light anti-condensation filler for interior use: for smoothing, renewing and filling interior surfaces. Avoids "cold wall effect" and offers thermal and acoustic insulation. Great performance and filling capacity. Excellent adhesion properties. Interior use.</p>	<p>Before application eliminate and clean mould from surfaces with Junoclean (Code 760.180). Layer thickness: any thickness. Working time: 2 hours. Theoretical performance: 0.6kg/m²/mm. Grey powder.</p>	10 kg	
<input type="checkbox"/> Light grey (77.302)				
<p>MRT-100 <i>Bonding & rendering</i></p> 	<p>Mortar for bonding and rendering thermal insulation boards. Fibre reinforced and flexible cement based mortar used for the application of various types of thermal insulating boards such as EPS, XPS and MW. Fibre reinforced. Excellent adhesion. High permeability to water vapour and high impact resistance.</p>	<p>Practical coverage - bonding: 3,5-4,5 kg/m² Practical coverage - rendering: 4-5 kg/m² for 3-5 mm thickness. White powder. Use interior/exterior. Part of the External Thermal Insulation Composite System (ETICS) JUNOTherm®.</p>	25 kg	
<input type="checkbox"/> White (77.600)				

Colourants, paint stripper, additives, etc

<p>COLOURANT</p> 	<p>Universal concentrated colourant. For interior and exterior use. Note: Vermilion red and Lemon yellow colourants are for interior use only.</p>	<p>Recommended for colouring all kinds of paint. The proportion of colourant in the paint should not exceed 3%.</p>	1 l	100 ml
<input type="checkbox"/> Lemon yellow* (79.404) <input type="checkbox"/> Black* (79.400) <input type="checkbox"/> Ochre yellow* (79.406) <input type="checkbox"/> Vermilion red* (79.402)				
<input type="checkbox"/> Blue* (79.401) <input type="checkbox"/> Oxide red* (79.403) <input type="checkbox"/> Shadow brown* (79.407) <input type="checkbox"/> Green* (79.405)				

<p>JUNO PAINT STRIPPER</p> 	<p>High performance, quick action paint stripper. Formulated with special solvents, free of methylene chloride. For interior and exterior use.</p>	<p>Recommended for quickly and conveniently removing most paints, enamels and varnishes. Its action is based on penetration between the paint film and the substrate, breaking the adhesion between both.</p>
		<p>4 l 750 ml 375 ml</p>
<p><input type="checkbox"/> Clear (83.100)</p>		<p>• • •</p>
<p>MISKY-MISKY <i>Fungicidal additive</i></p> 	<p>Fungicidal concentrate to protect decorative finishes from future mould attack. Formulated with heterocyclics, developing an intense prolonged broad spectrum action against moulds and algae.</p>	<p>Add at least one (100 ml) bottle to 15 litres of paint and stir or shake until product has been distributed and mixed evenly with the paint. Recommended as an additive to be mixed into emulsion paint, primer, undercoat, varnish, gloss, wallpaper paste, textured paint or tile adhesive to prevent the formation of mould.</p>
		<p>100 ml</p>
<p><input type="checkbox"/> White (79.597)</p>		<p>•</p>
<p>ANTI-SLIP MICROBEADS</p> 	<p>Anti-slip microbeads for floor coatings. Polypropylene microbeads with average diameter of 180 microns to improve the slip resistance of floor surfaces particularly when wet. Add a 150 gram tub for every 4L of paint, and 4 tubs for every 15 L of paint to achieve certified anti-slip protection.</p>	<p>This product gives the following product range from JUNO Class 3 Anti-slip rating: Dynapok agua Floor Epoxy (07.1...), Dynamol (09.5...), Junosol (06.1...), Pavimyc (07.8...), Junoretano (88.8...), and Junopoxi (88.8...). Add to the paint in the following proportion: 4 L (1 x 150 g) 15 L (1 x 600 g) or (4 x 150 g)</p>
		<p>600 gr 150 gr</p>
<p><input type="checkbox"/> White (07250)</p>		<p>• •</p>
<p>MICROBEADS FOR PAVIMYC HB 2/C</p> 	<p>Anti-slip microbeads for epoxy high-build floor coating systems. Polyethylene microbeads with an average diameter of 250 microns suitable for obtaining non-slip properties on wet surfaces.</p>	<p>Recommended as an anti-slip additive to obtain class 3 slip resistance in Pavimyc HB 2/C systems. Add a can of 400 grams for every 20 kg of paint.</p>
		<p>400 gr</p>
<p><input type="checkbox"/> Blanco (07251)</p>		<p>•</p>
<p>JUNOCLEAN</p> 	<p>JUNOCLEAN cleans interior and exterior mould and mildew stains fast. Sprayable for easy application. For interior and exterior use. Cleans stains fast and efficiently.</p>	<p>Ideal for use on masonry, brick, tiles, vinyl siding, wood, grout or other materials. Also ideal for kitchens, bathrooms and other spaces where organic dirt, mould and humidity is a problem. Available in larger packs upon request. Ask in-store for more information.</p>
		<p>New</p>
		<p>5 l 500 ml</p>
<p><input checked="" type="checkbox"/> Clean (760.180)</p>		<p>- •</p>
<p><input checked="" type="checkbox"/> Clean (760.183)</p>		<p>• -</p>
		<p>Supplied to order</p>

Thinners & cleaners

		20 l	5 l	1 l	500 ml
D-16 <i>White spirit</i>	Mineral thinner for synthetic products. Code (50.012)	•	•	•	•
D-17 <i>Quick drying</i>	Thinner for synthetic enamels and primers. Code (50.004)	•	•	•	-
D-40 <i>Chlorinated rubber</i>	Thinner for chlorinated rubber and pliolite enamels. Code (50.000)	•	•	•	-
D-45 <i>Universal</i>	Universal thinner. Code (50.017)	•	•	•	-
D-47 <i>Multi-purpose</i>	Thinner for professional use (cleaning). Code (50.019)	•	•	-	-
D-69 <i>Odourless</i>	Thinner for odourless stain block. Code (50.073)	-	•	•	-
D-70 <i>Polyurethane</i>	Thinner for polyurethane enamels and varnishes. Code (50.007)	•	•	•	-
D-71 <i>PU Retardant</i>	Retardant for polyurethane enamels and varnishes. Code (50.014)	•	•	•	-
D-75 <i>Retardant</i>	Retardant thinner. Code (50.107)	-	•	•	-
D-90 <i>Epoxy</i>	Thinner for epoxy enamels. Code (50.010)	•	•	•	-

Colour charts & fan decks

		1 Unit	
NCS 2050	Fan deck NCS Index 2050 Colours (Code 999.652)	•	
NCS 980	Fan deck NCS JUNO Selection 980 Colours (Code 999.651)	•	
RAL	RAL - JUNO colour selection fan deck (Code 999.631)	•	
JUNO COMBINA	COMBINA FAN DECK (Code 999.650)	•	
	COMBINA COLOUR CARD (Code 999.632)	•	
	POS RETAIL COMBINA COLOURS STAND (Code 999.543)	•	
EXTERIOR FAÇADES	Mini Fan deck - Exterior Colour collection (Code 999.547)	•	
	Colour Card - Exterior Colour collection (Code 999.628)	•	
	EXTERIOR COLOURS - POS RETAIL DISPLAY STAND (Code 999.666)	•	
COLOUR CARDS	JUNO colour cards	1 Unid.	
	JUNOKRIL Colour Card (999.636)	•	
	BIKRIL / LUNA Colour Card (999.620)	JUNOREV CHART (999.545)	•
	JUNOTINTE Colour Card (999.623)	FLOOR RANGE (999.637)	•
	LASUR Colour Card (999.624)		•
	JUNOLAC ANTI-OX Colour CARD (999.625)	OXIFORJA Colour Card (999.629)	•
	JUNOPLUS Colour Card (999.627)	AQUALAC Colour Card (999.839)	
	WATERPROOFING Colour Card (999.888)		

SU

PPLE

MEN

T
A
R
Y

SUPPLEMENTARY PRODUCTS

Special exterior coatings · Special interior coatings · Water-based 2K Polyurethane · Sealers/primers · Thinners · Varnish · Colourants - Tinting System

Special exterior coatings

Water-based

<p>JAKRILEN A-50 Matt</p> 	<p>High performance water-based paint. With anti-mould protection. Formulated with acrylic copolymers in aqueous dispersion. For interior and exterior use. Cleaning and dilution with water.</p> <p> EPD[®] THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (62.500)</p>	<p>Recommended for all types of constructions and ornaments. <i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p style="text-align: right;"></p> <p style="text-align: right;">15 l 4 l</p> <p style="text-align: right;">• •</p>
<p>A-4000 Matt</p> 	<p>Water-based paint. Formulated with copolymers in aqueous emulsion, with an anti-dust effect and matt finish. For interior and protected exterior use. Cleaning and dilution with water.</p> <p>  Product subject to availability. Variations in colours between batches may occur.</p> <p><input type="checkbox"/> Grey* (62.512)</p>	<p>Recommended for walls, bridges, tunnels, warehouses or car parks where a quality matt finish is required.</p> <p style="text-align: right;">15 l</p> <p style="text-align: right;">•</p>

Masonry coating

<p>MEDITERRANEAN FAÇADES Matt</p> 	<p>High-build water-based masonry coating. Formulated with acrylic-styrene copolymers. For interior and exterior use. Cleaning and dilution with water.</p> <p> EPD[®] THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (73.312)</p>	<p>Recommended for use outdoors in mild climates and for decorating interior warehouses, staircases, garages and places where a high build finish is required. Allows for fine stippling interior spaces. <i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p style="text-align: right;"></p> <p style="text-align: right;">15 l</p> <p style="text-align: right;">•</p>
--	--	---

Special interior coatings

Specialty paints

<p>J-35 EXTRA MATT <i>Extra-matt</i></p> 	<p>Extra-matt emulsion with enhanced opacity. With anti-mould protection.</p> <p>Formulated with premium acrylic copolymers to deliver a rich, ultra-matt finish. High quality, splatter-free application with excellent flow and levelling for a smooth, uniform result.</p> <p>Excellent washability. Suitable for interior use. Clean tools and dilute with water.</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (72.205)</p>	<p>Ideal for ceilings, workshops, warehouses, corridors and expansive areas where a perfectly uniform, ultra-matt finish is essential. Its anti-reflex properties minimise light reflection and surface glare, helping to disguise minor imperfections and deliver a flawless, professional appearance across large areas.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p> FIRE-RETARDANT B-s1,d0</p> <p>15 l</p>
<p>B-7 BLACK <i>Matt</i></p> 	<p>High-quality water-based emulsion.</p> <p>Formulated with premium acrylic copolymers and carefully selected black pigments to deliver a uniform black finish.</p> <p>Suitable for interior use. Clean tools and dilute with water.</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input checked="" type="checkbox"/> Black* (72.101)</p>	<p>Recommended for residential interiors, designer environments and commercial projects. Perfect for feature walls and for full black colour drenching, where ceilings, services and exposed elements are finished in black to create a seamless, architectural look. Ideal for retail spaces, hospitality venues, offices and contemporary living areas.</p> <p>Provides excellent opacity with outstanding resistance to wet abrasion and scuffing, ensuring long-lasting performance even in high-traffic settings.</p> <p><i>APPROVAL CERTIFICATES: Fire retardant to B-s1,d0 standard.</i></p> <p> FIRE-RETARDANT B-s1,d0</p> <p>15 l 4 l</p>
<p>CASTOR PICAR EXTRA <i>Matt</i></p> 	<p>Ready-to-use textured coating for decorative, stippled finishes.</p> <p>Formulated with high-performance acrylic copolymers, providing excellent hardness, strong adhesion and long-lasting durability. Designed to create an attractive textured surface that effectively conceals minor cracks, uneven areas and surface imperfections.</p> <p>Suitable for interior use. Clean tools and dilute with water.</p> <p> EPD® THE INTERNATIONAL EPD SYSTEM</p> <p><input type="checkbox"/> White (74.304)</p>	<p>Recommended for stairwells, corridors, public buildings, offices and residential interiors where a durable, hard-wearing finish is required. Ideal for high-traffic areas where both surface levelling and a robust decorative appearance are essential.</p> <p><i>APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Fire retardant to B-s1,d0 standard.</i></p> <p> FIRE-RETARDANT B-s1,d0</p> <p>15 l 4 l</p>

Water-based 2K polyurethane

AQUAPUR 2/C

Gloss / Satin



Two-pack water-based polyurethane coating.

Formulated based on polyurethane resins offering hard and resistant surfaces. Excellent levelling and resistance to rubbing. Robust weather resistant finish for exterior use.

Good flexibility and easy application.

Quick drying.

Interior and exterior use.

Cleaning and dilution with water.

For use on properly primed wood and metal surfaces. Recommended for all types of surfaces, especially wood carpentry such as kitchens, doors, window trims, skirting boards, etc. and for perfect smooth finishes on walls.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration) - Meets health related evaluation procedure for emissions of VOCs AgBB 2018 - A+ Certified - Fire retardant to B-s1,d0 standard.



4 l

White / Gloss (08.310)

•

White / Satin (08.315)

•

Sealers/primers

Sealers

QUICK DRYING STAIN BLOCK

Matt



Synthetic matt stain block with special resins.

Interior use.

Cleaning and dilution with Universal thinner D-45 (Code 50.017).

Recommended for all types of surfaces that have damp, grease, nicotine or other stains, or surfaces that have lost their hue. May be used as a quick drying primer for porous substrates or as a sealer/stain blocker. Seals porous surfaces with excellent enamel holdout.

15 l

4 l

750 ml

White (21.380)

•

•

•

Synthetic primer

“R” PRIMER

Matt



Economic synthetic primer.

Formulated with alkyd resins and iron oxides providing high opacity.

For interior and exterior use.

Cleaning and dilution with “Dilution for “R” primer” (Code 50.090).

Recommended for preparing ferrous surfaces, where an economic paint system is required.

Product subject to availability. Variations in colours between batches may occur.

15 l

4 l

Grey* (22.119)

•

•

Thinners

THINNER FOR “R” PRIMER

Diluent for “R” Primer and cleaning thinner for synthetic products.

Product subject to availability.

20 l

5 l

Code (50.090)

•

•

2K Clear polyurethanes

2K GRAF COATING

Gloss / Satin / Matt



Two-pack clear aliphatic polyurethane coating, available in gloss, satin and matt finishes.

Clean tools and dilute with Polyurethane Thinner D-70 (Code 50.007).

Suitable for interior and exterior use.

Recommended as a high-performance anti-graffiti coating, creating a durable protective barrier that allows graffiti to be removed quickly and easily without damaging the substrate.

Other uses include coating interior concrete floors and metal surfaces, and for areas where a premium, hard-wearing decorative finish is required. Provides excellent durability, UV resistance and long-term finish retention.

APPROVAL CERTIFICATES: EPD (Certified with Environmental Product Declaration).



- Clear / Gloss (44.270) Clear / Satin (44.271)
- Clear / Matt (44.272)

4 |

•

•

AQUAPUR PU VARNISH 2/C

Gloss / Satin / Matt



Two-pack water-based polyurethane varnish.

Delivers a tough, crystal-clear protective film with outstanding resistance to chemicals, wear and abrasion, while remaining easy to clean and maintain. Offers excellent hardness, fast drying and smooth, user-friendly application for a professional finish.

Suitable for interior use. Clean tools and thin with water.

Recommended for all types of parquet flooring and interior wooden surfaces, providing long-lasting protection without compromising the natural beauty of the wood.

Also suitable as a sealing and protective topcoat over 100% solids epoxy systems, including PAVIMYC HB flooring systems, enhancing durability and finish performance.



- Clear / Gloss (82.485)
- Clear / Satin (82.486)
- Clear / Matt (82.487)

4 |

•

•

•

Colourants - Tinting System

Colourants for Tinting System

JUNOMATIC

Colourant



JUNOMATIC Tinting System

Colourants for JUNO's Tintometric System.

Decorative Tintometric System

! Colourants for JUNOMALTE and JUNOPROF bases

1 |

- JS / Black (88.700)
- LS / Blue (88.701)
- MS / Yellow (88.702)
- NS / Red (88.703)
- PS / Green (88.704)
- QS / Intense yellow (88.705)
- RS / Intense blue (88.706)
- TS / Oxide ochre (88.707)
- US / Orange (88.708)
- VS / Intense red (88.709)
- WS / Oxide brown (88.710)
- XS / Grey (88.711)
- YS / Oxide red (88.712)
- ZS / Violet (88.713)
- KU / Oxide white (88.714)
- BS / Magenta (88.715)

Industrial Tintometric System

! Colourants for JUNORAPID, JUNOPOXI and JUNORETANO bases

1 |

- TBF / White (88.975)
- TAM / Oxide yellow (88.979)
- TEF / Oxide red (88.980)
- TAF / Medium yellow (88.986)
- TNA / Orange (89.980)
- TRO / Organic red (89.981)
- TUL / Blue (89.982)
- TVE / Green (89.983)
- TNG / Black (89.984)
- TMG / Magenta (89.985)
- TLL / Medium yellow (89.987)

MARKETED

PRODUCT RANGE

INTUMESCENT

PAINTS

MARKETED

PRODUCT RANGE

Intumescent paints

PRODUCTS

Intumescent paints

WIP PROMAPAIN SC3/SC4

Matt



Water-based reactive fire protective coating. Intumescent paint for fire protection of steel structures.

Reacts in the presence of and in contact with flames, forming an insulating foam, giving off salts with a fire fighting action.

For interior and exterior use. In exterior use finish with a proper paint

Product ready to use, do not dilute.

Cleaning with water.

Recommended for application on beams and open and closed metal sections, to provide a delay to the spread of fire of 30, 60, 90 or 120 minutes depending on the mass and microns applied.



25 kg

SC3 / White (89.053)

SC4 / White (89.054)

* Availability may vary by region.

NULLIFIRE

Matt



Water-based insulating intumescent paint, with a high resistance to fire.

Reacts in the presence of and in contact with flames, forming an insulating intumescence, giving off salts with a fire fighting action, preventing an easy ignition of combustible materials and delaying the destruction of metal structures, maintaining their mechanical properties.

For interior and exterior use. In exterior use finish with a proper paint

Product ready to use, do not dilute.

Cleaning with water.

Recommended for application on beams and open, closed or gapped metal sections, to provide a delay to the spread of fire depending on the mass and microns applied.



25 kg

SC803-90 / White (89.070)

* Availability may vary by region.

JUNO

PAINT MANUFACTURERS SINCE 1927



JUNO PAINTS LTD.
Unit 1, Zone 5 Clonminam Business
Park Portlaoise, Co. Laois
R32W2RW
Phone: (+353) 057 867 0634
info@junopaints.ie
www.junopaints.ie

JUNO PAINTS CENTRAL HQ
Barrio Saconi, 10
48950 Erandio (Bizkaia) SPAIN
Tel.: +34 944 670 062 - Fax: +34 944 675 832
infoweb@juno.es
www.junopaints.com
www.juno.es

