

Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# AQUAPUR 2/C BLANCO BRILLO COMP B - Código - 8310(B)



# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier:

AQUAPUR 2/C BLANCO BRILLO COMP B - Código - 8310(B)

# Other means of identification: UFI:

YOG0-H0KM-H000-VN7F

### 1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Decorative paint

Uses advised against: All uses not specified in this section or in section 7.3

### 1.3 Details of the supplier of the safety data sheet:

INDUSTRIAS JUNO, S.A. Barrio Sakoni, 10 48950 ERANDIO - Vizcaya - España Phone: +34 944 670 062 - Fax: +34 944 675 832 laboratorio@juno.es www.juno.es

### **1.4 Emergency telephone number:**

# SECTION 2: HAZARDS IDENTIFICATION \*\*

# 2.1 Classification of the substance or mixture:

### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute inhalation toxicity, Category 4, H332 Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412 Skin Sens. 1: Sensitisation, skin, Category 1, H317 STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

### 2.2 Label elements:

### CLP Regulation (EC) No 1272/2008:

Warning



# Hazard statements:

Acute Tox. 4: H332 - Harmful if inhaled. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation.

#### Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P302+P352: IF ON SKIN: Wash with plenty of water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

### Supplementary information:

EUH204: Contains isocyanates. May produce an allergic reaction.

### Additional Labelling:

As from 24 August 2023 adequate training is required before industrial or professional use.

### Acute Toxicity Estimate (ATE mix):

10,37 % (oral), 98,37 % (dermal), 10,37 % (inhalation) of the mixture consists of ingredient(s) of unknown toxicity

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -





# SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)

UFI: YQG0-H0KM-H000-VN7F

### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria Endocrine-disrupting properties: The product fails to meet the criteria.

\*\* Changes with regards to the previous version

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

Chemical description: Aqueous mixture composed of additives, coalescents, pigments and resins

#### **Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration
CAS:	28182-81-2	Hexamethylene diiso	cyanate, oligomers <sup>(1)</sup> Self-classified	
EC: Index: REACH:	931-274-8 Non-applicable 01-2119485796-17- XXXX	Regulation 1272/2008	Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning	75 - <90 %
CAS:	98-94-2	Cyclohexyldimethyla	mine <sup>(1)</sup> Self-classified	
EC: Index: REACH:			Acute Tox. 3: H301+H311+H331; Aquatic Chronic 2: H411; Eye Dam. 1: H318; Acute Tox. 3: H226; Skin Corr. 1B: H314 - Danger	1 - <10 %
CAS:	822-06-0	Hexamethylene-di-is	socyanate <sup>(1)</sup> Self-classified	
EC: Index: REACH:	212-485-8 615-011-00-1 01-2119457571-37- XXXX	Regulation 1272/2008	Acute Tox. 1: H330; Acute Tox. 4: H302; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	0,1 - <1 %

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

## Other information:

Identification	Specific concentration limit
	% (w/w) >=0,5: Resp. Sens. 1 - H334 % (w/w) >=0,5: Skin Sens. 1 - H317

\*\* Changes with regards to the previous version

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

# By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

#### By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Safety Data Sheet

#### By eye contact:





### SECTION 4: FIRST AID MEASURES (continued)

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

### Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

# Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

### Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

#### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### For emergency responders:

See section 8.

### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

### 6.3 Methods and material for containment and cleaning up:

#### It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.





# SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

### 6.4 Reference to other sections:

See sections 8 and 13.

# SECTION 7: HANDLING AND STORAGE

# 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum remp.:	5 %
Maximum Temp.:	30 °C
Maximum time:	24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

# 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

### DNEL (Workers):

		Short	exposure	Long	exposure
Identification		Systemic	Local	Systemic	Local
Hexamethylene diisocyanate, oligomers	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 28182-81-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 931-274-8	Inhalation	Non-applicable	1 mg/m <sup>3</sup>	Non-applicable	0,5 mg/m <sup>3</sup>
Cyclohexyldimethylamine	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 98-94-2	Dermal	Non-applicable	Non-applicable	0,6 mg/kg	Non-applicable
EC: 202-715-5	Inhalation	Non-applicable	8,3 mg/m <sup>3</sup>	0,53 mg/m <sup>3</sup>	8,3 mg/m <sup>3</sup>
Hexamethylene-di-isocyanate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 822-06-0	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 212-485-8	Inhalation	Non-applicable	0,07 mg/m <sup>3</sup>	Non-applicable	0,035 mg/m <sup>3</sup>

# DNEL (General population):

Non-applicable

- CONTINUED ON NEXT PAGE -





# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

#### PNEC:

Identification				
Hexamethylene diisocyanate, oligomers	STP	88 mg/L	Fresh water	0,127 mg/L
CAS: 28182-81-2	Soil	53183 mg/kg	Marine water	0,013 mg/L
EC: 931-274-8	Intermittent	1,27 mg/L	Sediment (Fresh water)	266701 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	26670 mg/kg
Cyclohexyldimethylamine	STP	20,6 mg/L	Fresh water	0,002 mg/L
CAS: 98-94-2	Soil	0,003 mg/kg	Marine water	0 mg/L
EC: 202-715-5	Intermittent	0,02 mg/L	Sediment (Fresh water)	0,021 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,002 mg/kg
Hexamethylene-di-isocyanate	STP	8,42 mg/L	Fresh water	Non-applicable
CAS: 822-06-0	Soil	Non-applicable	Marine water	Non-applicable
EC: 212-485-8	Intermittent	Non-applicable	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

### 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

### D.- Eye and face protection

	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
E Bo	ody protection				
	Pictogram	PPE	Labelling	CEN Standard	Remarks
		Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013. EN 464:1994.





- E						continued)		
	Pictogram		PPE	Labelling		CEN Standard		Remarks
		Anti-s	slip work shoes		E	N ISO 20347:2012	perioo recom	ce before any evidence of deterioration. F Is of prolonged exposure to the product fo professional/industrial users CE III is mended, in accordance with the regulatio EN ISO 20345:2012 y EN 13832-1:2007
F A	dditional emerge	ency mea	isures					
	Emergency mea	asure	St	andards		Emergency measu	ıre	Standards
	Emergency sho	ower		SI Z358-1 11, ISO 3864-4:20	11	Eyewash station	s	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
								nmended to avoid environmental
spilla <b>Vola</b>	nge of both the pr <b>tile organic co</b>	roduct a <b>mpounc</b>	nd its container. <b>Is:</b>	For additional i	nform	ation see subsectior		
spilla Vola	ige of both the p	roduct a <b>mpounc</b>	nd its container. <b>Is:</b>	For additional i	nform	ation see subsectior		
spilla <b>Vola</b> With	nge of both the pr <b>tile organic co</b>	roduct a <b>mpounc</b>	nd its container. <b>Is:</b> /75/EU, this prod	For additional i	nform	ation see subsectior		
spilla <b>Vola</b> With V	ige of both the pr itile organic con regard to Directi	roduct a <b>mpounc</b> ive 2010,	nd its container. <b>Is:</b> /75/EU, this prod 1,4 %	For additional i duct has the fol	nform llowing	ation see subsectior		
spilla <b>Vola</b> With V V	age of both the pr tile organic con regard to Directi 7.O.C. (Supply):	roduct an <b>mpounc</b> ive 2010, 20 °C:	nd its container. <b>Is:</b> /75/EU, this prod 1,4 %	For additional i duct has the fol 6 weight	nform llowing	ation see subsectior		
spilla <b>Vola</b> With V V A	age of both the provide the provided the pro	roduct an <b>mpounc</b> ive 2010, 20 °C: number:	nd its container. Is: (75/EU, this prod 1,4 % 15,26 8	For additional i duct has the fol 6 weight	nform llowing	ation see subsectior		
spilla <b>Vola</b> With V V A	age of both the provide the provided of both the provided to Direction (O.C. (Supply): 1/.0.C. density at the provided of the	roduct ar mpound ive 2010, 20 °C: number: ar weight	nd its container. <b>Is:</b> /75/EU, this prov 1,4 % 15,26 8 : 127,2	For additional i duct has the fol 6 weight 5 kg/m <sup>3</sup> (15,26 2 g/mol	nform llowing 5 g/L)	ation see subsectior	ז 7.1.D	
spilla <b>Vola</b> With V V A A With	age of both the provide the provided of both the provided to Direction (O.C. (Supply): 1/.0.C. density at the provided of the	roduct an <b>mpound</b> ive 2010, 20 °C: number: ar weight ive 2004,	nd its container. Is: /75/EU, this prov 1,4 % 15,26 8 : 127,2 /42/EC, this prov	For additional i duct has the fol 6 weight 5 kg/m <sup>3</sup> (15,26 2 g/mol	nform lowing g/L) eady to	ation see subsectior g characteristics:	ז 7.1.D	
spilla Vola With V A A With V	age of both the provide the provided the program of the provided to different terms of the provided terms of terms o	ive 2010, 20 °C: number: ar weight ive 2004, 20 °C:	nd its container. <b>Is:</b> /75/EU, this prod 1,4 % 15,26 8 : 127,2 /42/EC, this prod 15,26	For additional i duct has the fol weight 5 kg/m <sup>3</sup> (15,26 2 g/mol duct which is re 5 kg/m <sup>3</sup> (15,26	nform lowing g/L) eady to	ation see subsectior g characteristics:	ז 7.1.D	

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:	
Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	Not available
Odour:	Characteristic
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	171 °C
Vapour pressure at 20 °C:	148 Pa
Vapour pressure at 50 °C:	1063,72 Pa (1,06 kPa)
Evaporation rate at 20 °C:	Non-applicable *
Product description:	
Density at 20 °C:	1040 - 1140 kg/m³
Relative density at 20 °C:	1,04 - 1,14
Dynamic viscosity at 20 °C:	1200 cP
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 mm²/s
*Not relevant due to the nature of the product, not providing	g information property of its hazards.

Date of compilation: 09/10/2017





SEC	TION 9: PHYSICAL AND CHEMICAL PROPERTIES	S (continued)
	Concentration:	Non-applicable *
	pH:	Non-applicable *
	Vapour density at 20 °C:	Non-applicable *
	Partition coefficient n-octanol/water 20 °C:	Non-applicable *
	Solubility in water at 20 °C:	Non-applicable *
	Solubility properties:	Soluble in organic solvents
	Decomposition temperature:	Non-applicable *
	Melting point/freezing point:	Non-applicable *
	Flammability:	
	Flash Point:	40 °C
	Flammability (solid, gas):	Non-applicable *
	Autoignition temperature:	370 °C
	Lower flammability limit:	Non-applicable *
	Upper flammability limit:	Non-applicable *
	Particle characteristics:	
	Median equivalent diameter:	Non-applicable
9.2	Other information:	
	Information with regard to physical hazard clas	ses:
	Explosive properties:	Non-applicable *
	Oxidising properties:	Non-applicable *
	Corrosive to metals:	Non-applicable *
	Heat of combustion:	Non-applicable *
	Aerosols-total percentage (by mass) of flammable components:	Non-applicable *
	Other safety characteristics:	
	Surface tension at 20 °C:	Non-applicable *
	Refraction index:	Non-applicable *
	*Not relevant due to the nature of the product, not providing infor	mation property of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

# 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

# 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

# **10.3** Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

	midity
Not applicable      Not applicable      Precaution      Precaution	oplicable

# 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

# 10.6 Hazardous decomposition products:





# SECTION 10: STABILITY AND REACTIVITY (continued)

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide ( $CO_2$ ), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION \*\*

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

#### Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
  - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
  - IARC: Non-applicable
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
  - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as
  - it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

### Other information:

Non-applicable

### Specific toxicology information on the substances:

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -





# SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

Identification	A	Acute toxicity	
Cyclohexyldimethylamine	LD50 oral	289 mg/kg	Rat
CAS: 98-94-2	LD50 dermal	380 mg/kg	Rat
EC: 202-715-5	LC50 inhalation	3 mg/L (ATEi)	
Hexamethylene diisocyanate, oligomers	LD50 oral	5100 mg/kg	Rat
CAS: 28182-81-2	LD50 dermal	Non-applicable	
EC: 931-274-8	LC50 inhalation	11 mg/L (ATEi)	
Hexamethylene-di-isocyanate	LD50 oral	959 mg/kg	Rat
CAS: 822-06-0	LD50 dermal	7000 mg/kg	Rat
EC: 212-485-8	LC50 inhalation	0,12 mg/L (4 h)	Rat

# Acute Toxicity Estimate (ATE mix):

	Ingredient(s) of unknown toxicity	
Oral	18502,19 mg/kg (Calculation method)	10,37 %
Dermal	442,43 mg/kg (Calculation method)	98,37 %
Inhalation	8,68 mg/L (4 h) (Calculation method)	10,37 %

# **11.2** Information on other hazards:

# **Endocrine disrupting properties**

Endocrine-disrupting properties: The product fails to meet the criteria.

#### Other information

Non-applicable

\*\* Changes with regards to the previous version

# SECTION 12: ECOLOGICAL INFORMATION \*\*

The experimental information related to the eco-toxicological properties of the product itself is not available

### 12.1 Toxicity:

### Acute toxicity:

Identification	Concentration		Concentration Species	
Hexamethylene diisocyanate, oligomers		Non-applicable		
CAS: 28182-81-2	EC50	Non-applicable		
EC: 931-274-8	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae

\*\* Changes with regards to the previous version



Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

# AQUAPUR 2/C BLANCO BRILLO COMP B - Código - 8310(B)



#### SECTION 12: ECOLOGICAL INFORMATION \*\* (continued) Identification Concentration Species Genus Cyclohexyldimethylamine LC50 28 mg/L (96 h) Leuciscus idus Fish CAS: 98-94-2 EC50 75 mg/L (48 h) Crustacean Daphnia magna EC: 202-715-5 EC50 2 mg/L (72 h) Desmodesmus subspicatus Algae 12.2 Persistence and degradability: Identification Biodegradability Degradability Cyclohexyldimethylamine BOD5 Non-applicable Concentration 20 mg/L CAS: 98-94-2 COD Non-applicable Period 28 days EC: 202-715-5 BOD5/COD Non-applicable % Biodegradable 95 % 12.3 Bioaccumulative potential: Identification Bioaccumulation potential Cyclohexyldimethylamine BCF CAS: 98-94-2 Pow Log 2.31 EC: 202-715-5 Potential 12.4 Mobility in soil: Identification Absorption/desorption Volatility Koc 6,73 Pa·m³/mol 69.49 Henry Cyclohexyldimethylamine Dry soil CAS: 98-94-2 Conclusion High Non-applicable EC: 202-715-5 Surface tension Non-applicable Moist soil Non-applicable 12.5 Results of PBT and vPvB assessment: Product fails to meet PBT/vPvB criteria 12.6 Endocrine disrupting properties: Endocrine-disrupting properties: The product fails to meet the criteria. 12.7 Other adverse effects:

Not described

\*\* Changes with regards to the previous version

# SECTION 13: DISPOSAL CONSIDERATIONS

# **13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous





# SECTION 13: DISPOSAL CONSIDERATIONS (continued)

# Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising

### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

### **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# SECTION 14: TRANSPORT INFORMATION \*\*

### Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:


With regard to AL		1 anu RID 2021.				
•	14.1	UN number or ID number:	UN1263			
		UN proper shipping name:	PAINT			
	14.3	Transport hazard class(es):	3			
$\langle \simeq \rangle$		Labels:	3			
	14.4	Packing group:	III			
3	14.5	Environmental hazards:	No			
·	14.6	Special precautions for user				
		Special regulations:	163, 367, 650			
		Tunnel restriction code:	D/E			
		Physico-Chemical properties:	see section 9			
		Limited quantities:	5 L			
	14.7	Maritime transport in bulk	Non-applicable			
		according to IMO				
		instruments:				
Transport of dangerous goods by sea:						
With regard to IMDG 40-20:						
	14.1	UN number or ID number:	UN1992			
	14.2	UN proper shipping name:	FLAMMABLE LIQUID, TOXIC, N.O.S. (Cyclohexyldimethylamine;			
			Hexamethylene-di-isocyanate)			
3 6	14.3	Transport hazard class(es):	3			
▼ \\\/		Labels:	3, 6.1			
		Packing group:	III			
		Marine pollutant:	No			
	14.6	Special precautions for user				
		Special regulations:	274, 223			
		EmS Codes:	F-E, S-D			
		Physico-Chemical properties:	see section 9			
		Limited quantities:	5 L			
		Segregation group:	Non-applicable			
	14.7	Maritime transport in bulk according to IMO instruments:	Non-applicable			
Transport of dangerous goods by air:						
With regard to IATA/ICAO 2022:						

\*\* Changes with regards to the previous version





# SECTION 14: TRANSPORT INFORMATION \*\* (continued)



\*\* Changes with regards to the previous version

# SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

# Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):





# SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used in:

-ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains more than 0.1 % of Hexamethylene-di-isocyanate, Hexamethylene diisocyanate, oligomers by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or selfemployed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s).

2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".

3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks.

4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:

(a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).

- (b) the training elements in points (a) and (b) of paragraph 5 for the following uses:
- handling open mixtures at ambient temperature (including foam tunnels)
- spraying in a ventilated booth
- application by roller
  application by brush
- application by dipping and pouring
- mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore
- cleaning and waste
- any other uses with similar exposure through the dermal and/or inhalation route
- (c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:
- handling incompletely cured articles (e.g. freshly cured, still warm)
- foundry applications
- maintenance and repair that needs access to equipment
- open handling of warm or hot formulations (> 45 °C)

- spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers)

- and any other uses with similar exposure through the dermal and/or

inhalation route.

- 5. Training elements:
- (a) general training, including on-line training, on:
- chemistry of diisocyanates
- toxicity hazards (including acute toxicity)
- exposure to diisocyanates
- occupational exposure limit values
- how sensitisation can develop
- odour as indication of hazard
- importance of volatility for risk
- viscosity, temperature, and molecular weight of diisocyanates
- personal hygiene
- personal protective equipment needed, including practical instructions for its correct use and its limitations
- risk of dermal contact and inhalation exposure
- risk in relation to application process used
- skin and inhalation protection scheme
- ventilation
- cleaning, leakages, maintenance
- discarding empty packaging
- protection of bystanders
- identification of critical handling stages

- CONTINUED ON NEXT PAGE -





# SECTION 15: REGULATORY INFORMATION (continued)

- specific national code systems (if applicable)
- behaviour-based safety
- certification or documented proof that training has been successfully completed
- (b) intermediate level training, including on-line training, on:
- additional behaviour-based aspects
- maintenance
- management of change
- evaluation of existing safety instructions
- risk in relation to application process used
- certification or documented proof that training has been successfully completed
- (c) advanced training, including on-line training, on:
- any additional certification needed for the specific uses covered
- spraying outside a spraying booth
- open handling of hot or warm formulations (> 45 °C)
- certification or documented proof that training has been successfully completed

6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture (s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.

7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.

8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.

9. Member States shall include in their reports pursuant to Article 117(1) the following information:

(a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law

(b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates

- (c) national exposure limits for diisocyanates, if there are any
- (d) information about enforcement activities related to this restriction.

10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

### Other legislation:

The product could be affected by sectorial legislation

### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

### SECTION 16: OTHER INFORMATION \*\*

#### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

\*\* Changes with regards to the previous version





### SECTION 16: OTHER INFORMATION \*\* (continued) COMMISSION REGULATION (EU) 2020/878 COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12): New declared substances Hexamethylene diisocyanate, oligomers (28182-81-2) Cyclohexyldimethylamine (98-94-2) Hexamethylene-di-isocyanate (822-06-0) Removed substances Blocked Polyisocyanate Based on Hexamethylene Diisocyanate (HDI) (666723-27-9) CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16): Hazard statements · Supplementary information TRANSPORT INFORMATION (SECTION 14): UN number Packing group Texts of the legislative phrases mentioned in section 2: H332: Harmful if inhaled. H317: May cause an allergic skin reaction. H335: May cause respiratory irritation. H412: Harmful to aquatic life with long lasting effects. Texts of the legislative phrases mentioned in section 3: The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3 CLP Regulation (EC) No 1272/2008: Acute Tox. 1: H330 - Fatal if inhaled. Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled. Acute Tox. 4: H302 - Harmful if swallowed. Acute Tox. 4: H332 - Harmful if inhaled. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Eye Dam. 1: H318 - Causes serious eye damage. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 3: H226 - Flammable liquid and vapour. Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation. **Classification procedure:** Acute Tox. 4: Calculation method Skin Sens. 1: Calculation method STOT SE 3: Calculation method Aquatic Chronic 3: Calculation method Advice related to training: Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: http://echa.europa.eu http://eur-lex.europa.eu Abbreviations and acronyms:

\*\* Changes with regards to the previous version



Safety data sheet This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



# AQUAPUR 2/C BLANCO BRILLO COMP B - Código - 8310(B)

# SECTION 16: OTHER INFORMATION \*\* (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LOgPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

\*\* Changes with regards to the previous version

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified. - END OF SAFETY DATA SHEET -