



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

BARNIZ JUNOLAC MATE - Código - 42039



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: BARNIZ JUNOLAC MATE - Código - 42039

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Varnish

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

INDUSTRIAS JUNO, S.A.
Barrio Sakoni, 10
48950 ERANDIO - Vizcaya - España
Phone: +34 944 670 062 - Fax: +34 944 675 832
laboratorio@juno.es
www.juno.es

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Flam. Liq. 3: Flammable liquids, Category 3, H226

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1A: Sensitisation, skin, Category 1A, H317

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning



Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

Supplementary information:

Contains Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3- propanediamine and 1,3-propanediamine.

Substances that contribute to the classification

Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (CAS: 64742-48-9); Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 (CAS: 64742-95-6); Cobalt bis(2-ethylhexanoate) (CAS: 136-52-7)

Acute Toxicity Estimate (ATE mix):

- CONTINUED ON NEXT PAGE -



SECTION 2: HAZARDS IDENTIFICATION (continued)

51,11 % (dermal) of the mixture consists of ingredient(s) of unknown toxicity

UFI: YU80-10CV-000E-YAM9

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 64742-48-9 EC: 265-150-3 Index: 649-327-00-6 REACH: 01-2119486659-16-XXXX	Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7⁽¹⁾	ATP ATP01	25 - <45 %
	Regulation 1272/2008	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger	
CAS: 112945-52-5 EC: Non-applicable Index: Non-applicable REACH: 01-2119379499-16-XXXX	Syntetic Silicon Dioxide⁽¹⁾	Self-classified	1 - <10 %
	Regulation 1272/2008	Eye Irrit. 2: H319; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning	
CAS: 64742-95-6 EC: 265-199-0 Index: 649-356-00-4 REACH: 01-2119486773-24-XXXX	Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7⁽¹⁾	ATP ATP01	1 - <10 %
	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H336; EUH066 - Danger	
CAS: 64742-48-9 EC: 265-150-3 Index: 649-327-00-6 REACH: 01-2119486659-16-XXXX	Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7⁽¹⁾	ATP ATP01	1 - <10 %
	Regulation 1272/2008	Asp. Tox. 1: H304; EUH066 - Danger	
CAS: 22464-99-9 EC: 245-018-1 Index: Non-applicable REACH: 01-2119979088-21-XXXX	2-ethylhexanoic acid, zirconium salt⁽¹⁾	Self-classified	0,1 - <1 %
	Regulation 1272/2008	Repr. 2: H361d - Warning	
CAS: 2457-01-4 EC: 219-535-8 Index: Non-applicable REACH: 01-2119983179-22-XXXX	Barium bis(2-ethylhexanoate)⁽¹⁾	Self-classified	0,1 - <1 %
	Regulation 1272/2008	Eye Dam. 1: H318; Repr. 2: H361d - Danger	
CAS: 162627-17-0 EC: Non-applicable Index: Non-applicable REACH: 01-2119970640-38-XXXX	Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine⁽¹⁾	Self-classified	0,1 - <1 %
	Regulation 1272/2008	Skin Sens. 1: H317 - Warning	
CAS: 107-98-2 EC: 203-539-1 Index: 603-064-00-3 REACH: 01-2119457435-35-XXXX	1-methoxy-2-propanol⁽²⁾	ATP ATP01	0,1 - <1 %
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	
CAS: 34590-94-8 EC: 252-104-2 Index: Non-applicable REACH: 01-2119450011-60-XXXX	Dipropylene Glycol Methyl Ether⁽²⁾	Not classified	0,1 - <1 %
	Regulation 1272/2008		

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Substance with a Union workplace exposure limit

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



BARNIZ JUNOLAC MATE - Código - 42039

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)

Identification	Chemical name/Classification	Concentration
CAS: 136-52-7 EC: 205-250-6 Index: Non-applicable REACH: 01-2119524678-29-XXXX	Cobalt bis(2-ethylhexanoate)⁽¹⁾ Self-classified	0,1 - <1 %
	Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 1B: H360; Skin Sens. 1A: H317 - Danger	
CAS: 136-53-8 EC: 205-251-1 Index: Non-applicable REACH: 01-2119979071-36-XXXX	Zinc bis(2-ethylhexanoate)⁽¹⁾ Self-classified	0,1 - <1 %
	Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Repr. 2: H361d - Warning	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878
⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

** Changes with regards to the previous version

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

- CONTINUED ON NEXT PAGE -

**BARNIZ JUNOLAC MATE - Código - 42039****SECTION 5: FIREFIGHTING MEASURES (continued)**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:****A.- General precautions for safe use**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:**A.- Technical measures for storage**

- CONTINUED ON NEXT PAGE -



BARNIZ JUNOLAC MATE - Código - 42039

SECTION 7: HANDLING AND STORAGE (continued)

Minimum Temp.: 5 °C
 Maximum Temp.: 30 °C
 Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits		
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1		IOELV (8h)	100 ppm	375 mg/m ³
		IOELV (STEL)	150 ppm	568 mg/m ³
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2		IOELV (8h)	50 ppm	308 mg/m ³
		IOELV (STEL)		

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1286,4 mg/m ³	1066,67 mg/m ³	Non-applicable	837,5 mg/m ³
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1286,4 mg/m ³	1066,67 mg/m ³	Non-applicable	837,5 mg/m ³
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1286,4 mg/m ³	1066,67 mg/m ³	Non-applicable	837,5 mg/m ³
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	6,49 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	32,97 mg/m ³	Non-applicable
Barium bis(2-ethylhexanoate) CAS: 2457-01-4 EC: 219-535-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	7,25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	20,49 mg/m ³	Non-applicable
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	183 mg/kg	Non-applicable
	Inhalation	553,5 mg/m ³	553,5 mg/m ³	369 mg/m ³	Non-applicable
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	283 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	308 mg/m ³	Non-applicable
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,2351 mg/m ³

- CONTINUED ON NEXT PAGE -



BARNIZ JUNOLAC MATE - Código - 42039

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Zinc bis(2-ethylhexanoate) CAS: 136-53-8 EC: 205-251-1	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,46 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	17,33 mg/m ³	Non-applicable

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1152 mg/m ³	640 mg/m ³	Non-applicable	178,57 mg/m ³
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1152 mg/m ³	640 mg/m ³	Non-applicable	178,57 mg/m ³
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	1152 mg/m ³	640 mg/m ³	Non-applicable	178,57 mg/m ³
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	Oral	Non-applicable	Non-applicable	4,51 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	3,25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	8,13 mg/m ³	Non-applicable
Barium bis(2-ethylhexanoate) CAS: 2457-01-4 EC: 219-535-8	Oral	Non-applicable	Non-applicable	3,62 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	3,62 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	6,06 mg/m ³	Non-applicable
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	Oral	Non-applicable	Non-applicable	33 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	78 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	43,9 mg/m ³	Non-applicable
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	121 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	37,2 mg/m ³	Non-applicable
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	Oral	Non-applicable	Non-applicable	0,175 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	0,037 mg/m ³
Zinc bis(2-ethylhexanoate) CAS: 136-53-8 EC: 205-251-1	Oral	Non-applicable	Non-applicable	1,23 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1,23 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	4,27 mg/m ³	Non-applicable

PNEC:

Identification					
Fatty acids, C18, unsatd., dimers, reaction products with N,N-dimethyl-1,3- propanediamine and 1,3-propanediamine CAS: 162627-17-0 EC: Non-applicable	STP	Non-applicable	Fresh water	Non-applicable	
	Soil	5,8 mg/kg	Marine water	Non-applicable	
	Intermittent	Non-applicable	Sediment (Fresh water)	Non-applicable	
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable	
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	STP	100 mg/L	Fresh water	10 mg/L	
	Soil	4,59 mg/kg	Marine water	1 mg/L	
	Intermittent	100 mg/L	Sediment (Fresh water)	52,3 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	5,2 mg/kg	
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	STP	4168 mg/L	Fresh water	19 mg/L	
	Soil	2,74 mg/kg	Marine water	1,9 mg/L	
	Intermittent	190 mg/L	Sediment (Fresh water)	70,2 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	7,02 mg/kg	

- CONTINUED ON NEXT PAGE -



BARNIZ JUNOLAC MATE - Código - 42039

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



Identification				
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	STP	0,37 mg/L	Fresh water	0,00062 mg/L
	Soil	10,9 mg/kg	Marine water	0,00236 mg/L
	Intermittent	Non-applicable	Sediment (Fresh water)	53,8 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	69,8 mg/kg
Zinc bis(2-ethylhexanoate) CAS: 136-53-8 EC: 205-251-1	STP	0,53763 mg/L	Fresh water	0,11075 mg/L
	Soil	1,3 mg/kg	Marine water	0,0328 mg/L
	Intermittent	Non-applicable	Sediment (Fresh water)	7,83 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,78 mg/kg

8.2 Exposure controls:



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2002 EN ISO 14116:2015 EN 1149-5:2018	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -



BARNIZ JUNOLAC MATE - Código - 42039

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	38,06 % weight
V.O.C. density at 20 °C:	353,93 kg/m ³ (353,93 g/L)
Average carbon number:	8,95
Average molecular weight:	128,13 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	366,9 kg/m ³ (366,9 g/L)
EU limit for the product (Cat. A.E):	400 g/L (2010)
Components:	Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	Yellowish
Odour:	Characteristic
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	156 °C
Vapour pressure at 20 °C:	450 Pa
Vapour pressure at 50 °C:	2552,92 Pa (2,55 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	880 - 980 kg/m ³
Relative density at 20 °C:	Non-applicable *
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 mm ² /s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Solubility properties: Soluble in organic solvents

Decomposition temperature: Non-applicable *

Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: 27 °C

Flammability (solid, gas): Non-applicable *

Autoignition temperature: 200 °C

Lower flammability limit: Not available

Upper flammability limit: Not available

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Non-applicable *

Oxidising properties: Non-applicable *

Corrosive to metals: Non-applicable *

Heat of combustion: Non-applicable *

Aerosols-total percentage (by mass) of flammable components: Non-applicable *

Other safety characteristics:

Surface tension at 20 °C: Non-applicable *

Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

- CONTINUED ON NEXT PAGE -



BARNIZ JUNOLAC MATE - Código - 42039

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Hydrocarbons, C9, aromatics (3); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3); Cobalt bis(2-ethylhexanoate) (2B); Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 (3); Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 (3); Polyethylene wax (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Syntetic Silicon Dioxide CAS: 112945-52-5 EC: Non-applicable	LD50 oral	10000 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

BARNIZ JUNOLAC MATE - Código - 42039**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

Identification	Acute toxicity		Genus
	Route	Dose	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	LD50 oral	15000 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	LD50 oral	15000 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	2000 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	LD50 oral	2043 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	9510 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
Zinc bis(2-ethylhexanoate) CAS: 136-53-8 EC: 205-251-1	LD50 oral	2043 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	15044,31 mg/kg (Calculation method)	51,11 %
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

11.2 Information on other hazards:**Endocrine disrupting properties**

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

- CONTINUED ON NEXT PAGE -



BARNIZ JUNOLAC MATE - Código - 42039

SECTION 12: ECOLOGICAL INFORMATION (continued)

Acute toxicity:

Identification	Concentration		Species	Genus
	LC50			
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	LC50	2200 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1000 mg/L (96 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Syntetic Silicon Dioxide CAS: 112945-52-5 EC: Non-applicable	LC50	10000 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	10000 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	LC50	>1 - 10 (96 h)		Fish
	EC50	>1 - 10 (48 h)		Crustacean
	EC50	>1 - 10 (72 h)		Algae
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	LC50	2200 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1000 mg/L (96 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	LC50	270 mg/L (96 h)	N/A	Fish
	EC50	Non-applicable		
	EC50	Non-applicable		
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	LC50	20800 mg/L (96 h)	Pimephales promelas	Fish
	EC50	23300 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (168 h)	Selenastrum capricornutum	Algae
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	LC50	10000 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1919 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	LC50	>0.1 - 1 (96 h)		Fish
	EC50	>0.1 - 1 (48 h)		Crustacean
	EC50	>0.1 - 1 (72 h)		Algae
Zinc bis(2-ethylhexanoate) CAS: 136-53-8 EC: 205-251-1	LC50	107 mg/L (96 h)	N/A	Fish
	EC50	16 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		

Chronic toxicity:

Identification	Concentration		Species	Genus
	NOEC			
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	NOEC	Non-applicable		
	NOEC	25 mg/L	Daphnia magna	Crustacean

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



BARNIZ JUNOLAC MATE - Código - 42039

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
	NOEC	Non-applicable		
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	NOEC	0,5 mg/L	Daphnia magna	Crustacean
Cobalt bis(2-ethylhexanoate) CAS: 136-52-7 EC: 205-250-6	NOEC	0,21 mg/L	Pimephales promelas	Fish
	NOEC	0,1697 mg/L	Aeolosoma sp.	Crustacean
Zinc bis(2-ethylhexanoate) CAS: 136-53-8 EC: 205-251-1	NOEC	0,025 mg/L	Clupea harengus	Fish
	NOEC	0,101 mg/L	Americamysis bahia	Crustacean

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
	BOD5	Non-applicable	Concentration	Non-applicable
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	89,9 %
	BOD5	0,19 g O2/g	Concentration	Non-applicable
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	COD	0,44 g O2/g	Period	Non-applicable
	BOD5/COD	0,43	% Biodegradable	Non-applicable
	BOD5	Non-applicable	Concentration	Non-applicable
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	89,9 %
	BOD5	Non-applicable	Concentration	20 mg/L
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	99 %
	BOD5	Non-applicable	Concentration	100 mg/L
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %
	BOD5	Non-applicable	Concentration	Non-applicable
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	COD	0 g O2/g	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	73 %
	BOD5	Non-applicable	Concentration	Non-applicable
Zinc bis(2-ethylhexanoate) CAS: 136-53-8 EC: 205-251-1	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	60 %

12.3 Bioaccumulative potential:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



BARNIZ JUNOLAC MATE - Código - 42039

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulation potential	
Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 CAS: 64742-95-6 EC: 265-199-0	BCF	
	Pow Log	4
	Potential	
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	BCF	
	Pow Log	2.96
	Potential	
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	BCF	3
	Pow Log	-0.44
	Potential	Low
Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2	BCF	1
	Pow Log	-0.06
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Koc	100	Henry	Non-applicable
	Conclusion	High	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
Naphtha (petroleum), hydrotreated heavy, < 0.1 % EC 200-753-7 CAS: 64742-48-9 EC: 265-150-3	Koc	100	Henry	Non-applicable
	Conclusion	High	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
2-ethylhexanoic acid, zirconium salt CAS: 22464-99-9 EC: 245-018-1	Koc	Non-applicable	Henry	2,94E-1 Pa·m ³ /mol
	Conclusion	Non-applicable	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

- CONTINUED ON NEXT PAGE -



SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Special regulations: 163, 367, 650
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: 223, 955, 163, 367
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Non-applicable
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



- 14.1 UN number or ID number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable
 Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
 Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

BARNIZ JUNOLAC MATE - Código - 42039



SECTION 15: REGULATORY INFORMATION (continued)

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

- Removed substances
2-butanone oxime (96-29-7)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Substances contained in EUH208:
 - Removed substances
2-butanone oxime (96-29-7)

Texts of the legislative phrases mentioned in section 2:

H336: May cause drowsiness or dizziness.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H412: Harmful to aquatic life with long lasting effects.

H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

BARNIZ JUNOLAC MATE - Código - 42039



SECTION 16: OTHER INFORMATION (continued)

Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Repr. 1B: H360 - May damage fertility or the unborn child.
Repr. 2: H361d - Suspected of damaging the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
STOT SE 3: H335 - May cause respiratory irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

STOT SE 3: Calculation method
Skin Irrit. 2: Calculation method
Skin Sens. 1A: Calculation method
Aquatic Chronic 3: Calculation method
Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -