

Technical Datasheet

NATURSELL

JUNO

Product Code: 21100 Enamels/ Sealers & Stain Covers

DESCRIPTION

Water-based primer undercoat special for wood.

Formulated with acrylic resins in aqueous dispersion with great resistance and high opacity.

USE: INTERIOR - EXTERIOR

Recommended for use as a primer for carpentry and wood derivative surfaces such as softwoods, hardwoods, chipboards and fibre boards.

PROPERTIES

- Excellent coverage and brushability
- Seals porous surfaces, facilitating an even topcoat finish
- Improves adhesion and uniformity for successive coats
- Great sealing and filling power
- Good leveling

Finish: Matt

Colour: White

Viscosity: Min. 38 P S/FR1007

Density: 1,3 ± 0,05 g/cc S/FR1001

Drying: Touch dry 1-2 hours

Minimum repaint time: 12 hours

Maximum repaint time: Unlimited

Thinner: Water

Practical coverage: 8-10 m²/L (per coat)

Tinting: Juno Universal Colourant (max. 3%)

Solids in volume: 42 ± 2 %. Theoretical - White

Flash point: Not flammable (>60 °C)

VOC Content: Maximum 50 g/l

21100 WHITE



Formats: 0,750L / 4L

The information contained in this data sheet may change and must be updated. Consult www.juno.es or your nearest JUNO representative to obtain the most recent data sheet. The technical advice of application, whether verbal, written or through trials, are based on the experience and technical knowledge of JUNO. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, employment and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the client, applicator or manipulator of the products and not of the supplying company. This document does not exempt the client from carrying out his own examination of the products supplied, in order to verify their suitability for the procedures and intended purposes. In case of responsibility assumed by JUNO, it will be limited to the strict value of the goods supplied and used by the customer, whatever the damages and losses caused. JUNO guarantees the quality of all its products, in accordance with the current General Sales Conditions.

Technical Datasheet

NATURSELL



Product Code: 21100 Enamels/ Sealers & Stain Covers

SURFACE PREPARATION

WOOD. Surface must be grease/oil free, clean and completely dry. Sand wood if necessary and leave surface free of dust and foreign particles. Surface moisture content shall not exceed 15%.

MASONRY. Surface must be dry and free of efflorescence and, in the case of cement and gypsum, neutralize with 10% hydrochloric acid. Rinse with water as level to fully dry.

PAINTED SURFACES. If paint is in good condition Naturesell can be applied directly, after washing and smooth sanding to completely eliminate any gloss. Always carry out this operation to avoid surface tension, cracking problems and lack of adhesion. If existing paint is in poor condition, remove completely using **JUNO Paint Remover (Prod. Code 83.100)**. Clean, rinse and proceed as with unpainted surfaces.

PATHOLOGIES.

Mould contamination. Clean stains thoroughly and disinfect using **Junoclean (Prod.Code 760.180)**. Rinse with clean water and leave to dry out completely.

Salt efflorescence (saltpeter). Brush energetically, wash and neutralize with a solution of hydrochloric acid or zinc sulfate (10%). Rinse with water and let dry completely.

APPLICATION TIPS

Stir the content until total homogenization. Apply on clean surfaces, completely dry, free of efflorescence (saltpeter) and molds. Dilute the product depending on porosity and state of the treated surface.

ENVIRONMENTAL CONDITIONS. Do not apply at temperatures below 5°C, nor on excessively warm surfaces. The temperature of the substrate must be at least 3 °C above the dew point. The relative humidity should not exceed 80%. Do not apply when risk of rain or strong wind.

APPLICATION METHOD. Brush, roller or spray equipment.

CLEANING. Clean stains immediately and wash work tools with soap and water.

SAFETY & ENVIRONMENT

Minimize product waste by estimating the correct amount needed, taking into account the m², porosity and texture of the surface. Store any excess material (unmixed) in a ventilated and dry place. The container must be clean and of adequate size for the amount of product left over.

Close containers carefully and keep upright to avoid spills. Preserve the containers of frost, high temperatures and direct exposure to the sun. Keep any unused product for later use to reduce environmental effects.

Do not eat, drink or smoke during the preparation and application of the product. Surface preparation and application operations must be carried out with the corresponding safety measures. For more information, consult the Safety Data Sheet. In case of contact with eyes wash with clean and abundant water.

Keep out of the reach of children.

Do not discharge into drains or the environment. Dispose of at an authorized waste collection point.

Consult your local city council about the correct recycling of both the container and waste and leftovers of paint according to law and principles of environmental respect.

The information contained in this data sheet may change and must be updated. Consult www.juno.es or your nearest JUNO representative to obtain the most recent data sheet. The technical advice of application, whether verbal, written or through trials, are based on the experience and technical knowledge of JUNO. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, employment and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the client, applicator or manipulator of the products and not of the supplying company. This document does not exempt the client from carrying out his own examination of the products supplied, in order to verify their suitability for the procedures and intended purposes. In case of responsibility assumed by JUNO, it will be limited to the strict value of the goods supplied and used by the customer, whatever the damages and losses caused. JUNO guarantees the quality of all its products, in accordance with the current General Sales Conditions.