

Technical Data Sheet

STAIN COVER - TAPA-MANCHAS

JUNO

Product Code: 21350 Enamels/ Sealers and Stain Covers

DESCRIPTION

Synthetic Odourless Stain Cover. Formulation based on high quality Plioway resins with anti-stain and anti-mould preventive action.

USE: INTERIOR

Recommended for any surface stained by damp, smoke, nicotine, etc.

Its many applications include:

- Stain cover / brightener for dingy or faded ceiling tiles
- Paint sealer or primer for new drywall and plaster
- Cover for rough surfaces like masonry substrates

PROPERTIES

- Matt Finish
- Excellent whiteness and opacity
- Great adhesion power
- Insulates and covers stains from humidity, grease, nicotine etc.
- Washable
- Resistant to yellowing
- Anti-mould prevention
- Breathable
- No dripping or sagging

Finish: Matt**Colour:** WHITE**Viscosity:** Minimum 120 P S/FR1007**Density:** 1,38 ± 0,05 g/cc S/FR1001**Drying:** Touch dry in 4 hours**Minimum repaint time:** 24 hours**Maximum repaint time:** Unlimited**Thinner:** JUNO D-69**Practical Coverage:** 7,5 m²/L (per coat)**Solids in volume:** 39,5 ± 2 %. Theoretical (White)**Flash Point:** Inflammable 43 °C**VOC Content :** Maximum 480 g/l

21350 WHITE



Format: 0,750L / 4L / 15L

The information contained in this data sheet may change and is correct at the time of publishing. Consult www.junopaints.com or your nearest JUNO representative to obtain the most recent data sheet. The technical advice of application, whether verbal, written or through tests, are based on the experience and technical knowledge of JUNO. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, use and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the client, applicator or users of the products and not of the supplying company. This document does not exempt the client from carrying out their own examination of the products supplied, in order to verify their suitability for the procedures and intended purposes. In case of responsibility assumed by JUNO, it will be limited to the strict value of the goods supplied and used by the customer, whatever the damages and losses caused. JUNO guarantees the quality of all its products, in accordance with the current General Sales Conditions.

Industrias JUNO, S.A. • Barrio Sakoni, 10 • 48950 Erandio (Bizkaia), Spain • Tel. (+34) 944 670 062 • infoweb@juno.es • www.junopaints.com

Technical Data Sheet

STAIN COVER - TAPA-MANCHAS



Product Code: 21350 Enamels/ Sealers and Stain Covers

SURFACE PREPARATION

WOOD. Interior only. Must be clean and dry, grease-free and sanded. Humidity content must be less than 15%.

IRON & STEEL. Remove grease and rust, and prime with **Multi-support primer(Prod.Code 27.040)**.

ALUMINIUM & GALVANIZED. If hot-dip galvanized surfaces have been exposed to the atmosphere, they form zinc corrosion (white rust) and contaminants can accumulate. These must be removed by washing with fresh, clean water containing detergents and by using abrasive synthetic fibres to remove any corrosion. Finish off by thorough cleaning using hot water. Alternatively, the use of hot water, pressurized water, steam cleaning, sweep blasting or cleaning with manual or mechanical tools may be suitable. Sand surface and remove any generated dust. Given the wide variety of types of galvanizing in the market, it is recommended to carry out a test patch to check the strength and adhesion of the primer first, and to detect any possible incompatibilities before proceeding with the whole process. Once ensuring surface is completely clean and dry, apply a coat of **Multi-support primer (Prod. Code 27.040)**.

MASONRY. UNTREATED SURFACES. Must be dry, clean, porous and free of efflorescence and, in case of cement and gypsum neutralize with 10% hydrochloric acid. For fixing, hardening and sealing of powdery surfaces, apply one coat of **AkriI-80 (42.115)**.

PAINTED SURFACES. Shiny surfaces or gloss paints; sand to remove gloss to promote adhesion and eliminate surface tensions. Perform a test to check the strength and adhesion of the paint and to prevent possible incompatibilities between different paint layers. If the paint is in good condition, it can be painted onto directly, after washing and soft sanding to completely eliminate any gloss. If the paint is in poor condition, it must be completely removed. Next, follow directions of use for new surfaces.

PATHOLOGIES.

Mould contamination. Remove all mildew from the surface by disinfecting and cleaning thoroughly using **Junoclean (Prod. Code 760.180)**. Rinse thoroughly, and leave to dry.

Efflorescence/Salts. Use a brush or sponge and scrub the area. Wash and neutralize using chloridic acid or zinc sulphate solution (10%). Rinse with clean water, and leave to dry completely.

APPLICATION TIPS

Stir the contents of the container until complete homogenization. Apply to clean surfaces, completely dry, free of efflorescence and mould.

ENVIRONMENTAL CONDITIONS. Do not use in extremes of temperatures (below 5°C or hot temperatures). Surface temperature must be at least 3 °C above dew point, and the relative humidity must not exceed 80%. Do not apply when there is risk of rain, fog or strong wind.

APPLICATION METHOD. Brush or roller. For best results, apply minimum two undiluted coats.

LIMPIEZA. Immediately clean stains and application tools with **D-69 Thinner (Prod.Code 50.073)** or **D-16 Thinner (Prod.Code 50.012)**.

OBSERVATIONS

Stain Cover is normally used as a topcoat, however it can be topcoated with emulsion paint. When overcoating Stain Cover with water-based emulsions 30 days within application, old stains may reappear, as the water content may draw them back to the surface.

At temperatures below 5°C, adding D-69 Odourless Thinner (Prod.Code 50.073) may give problems in mixing the two components together properly due to the low temperature. If thinner is required at such low temperatures, use the D-16 thinner (Prod.Code 50.012), although this thinner may emit some odours.

SAFETY AND ENVIRONMENT

Solvent based products must be applied with good ventilation and with the necessary protection measures. Avoid sources of ignition. Minimize product waste by estimating the amount needed, taking into account the m², porosity and the surface texture. Store the excess material in a ventilated and dry place. The container must be clean and of adequate size for the amount of product left over. Close containers carefully and keep upright to avoid spills. Preserve the containers from frost, high temperatures and direct exposure to the sun. Do not eat, drink or smoke during the preparation and application of the product. Surface preparation and application operations must be carried out with the corresponding safety measures. For more information, consult the Safety Data Sheet. In case of contact with eyes wash with clean and abundant water. Keep out of the reach of children. Do not discharge into drains or the environment. Dispose to an authorized waste collection point. Consult your town hall about the correct recycling of both the container and waste and leftovers of paint according to law and principles of environmental respect.

The information contained in this data sheet may change and is correct at the time of publishing. Consult www.junopaints.com or your nearest JUNO representative to obtain the most recent data sheet. The technical advice of application, whether verbal, written or through tests, are based on the experience and technical knowledge of JUNO. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, use and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the client, applicator or users of the products and not of the supplying company. This document does not exempt the client from carrying out their own examination of the products supplied, in order to verify their suitability for the procedures and intended purposes. In case of responsibility assumed by JUNO, it will be limited to the strict value of the goods supplied and used by the customer, whatever the damages and losses caused. JUNO guarantees the quality of all its products, in accordance with the current General Sales Conditions.

Industrias JUNO, S.A. • Barrio Sakoni, 10 • 48950 Erandio (Bizkaia), Spain • Tel. (+34) 944 670 062 • infoweb@juno.es • www.junopaints.com

June 2016 Rev. 09

2 / 2