

Technical datasheet

D-17 Quick-dry thinner

JUNO

Product Code: 50004 Thinners

DESCRIPTION

Thinner for synthetic enamels and primers.
Formulated with a blend of aromatic hydrocarbons.

USE

For thinning polyurethane enamels and varnishes.
Suitable for thinning synthetic, pliolite, and chlorinated rubber enamels.
Also recommended for cleaning application tools.
Use only with products for which it is specified in the technical data sheet.

PROPERTIES

- Suitable evaporation rate for a uniform finish
- Perfect balance between surface and internal drying
- Adjusts viscosity in the specified paints
- High cleaning and dissolving power

Colour: Clear**Density:** 0,87 ± 0,05 g/cc S/FR1001**Flash point:** Easily flammable (25 °C)

50004 CLEAR



Format: 1 / 5 / 20 L

SURFACE PREPARATION

Follow the instructions provided for the paint with which this product is recommended.

APPLICATION TIPS

THINNING: Add the recommended amount as specified in the technical data sheet of the product to be thinned. Stir the mixture slowly until fully homogeneous.

CLEANING: Clean tools immediately after use to prevent the paint from drying. Thoroughly remove all paint residues, then wash the equipment with soapy water.
Allow the tools to dry completely.

SAFETY & ENVIRONMENT

This product must be handled in a well-ventilated area using appropriate protective equipment. Keep away from sources of ignition. Do not inhale vapours. Avoid contact with skin and eyes by wearing protective gloves and safety goggles. In case of splashes, rinse immediately and thoroughly with plenty of water. For more information, please refer to the Safety Data Sheet.

Store any leftover material in a dry, well-ventilated place. Ensure containers are tightly sealed and stored upright to prevent spills. Protect containers from frost, excessive heat, and direct sunlight.

Do not eat, drink, or smoke while preparing or applying the product. Keep out of reach of children.

Do not dispose of into drains or the environment. Dispose of waste only at authorised collection points.

Please consult your local authority regarding the correct disposal and recycling of containers, waste, and leftover product in accordance with legal requirements and environmental best practices.

The information contained in this technical data sheet may be subject to change and should be regularly updated. Please visit [www.juno.es, or contact your nearest JUNO representative to obtain the most recent technical data sheet. Technical application advice, whether given verbally, in writing, or through testing, is based on JUNO's experience and technical knowledge. The data provided in this document should be regarded as a recommendation only and does not constitute any form of guarantee or commitment, including with respect to potential third-party intellectual property rights. The application, use, and processing of JUNO products are carried out by third parties. Consequently, the final result is the sole responsibility of the customer, applicator, or handler of the products, and not of the supplying company. This document does not exempt the customer from conducting their own evaluation of the supplied products to verify their suitability for the intended procedures and purposes. In the event of any liability accepted by JUNO, it shall be limited strictly to the value of the goods supplied and used by the customer, regardless of any damages or losses incurred. JUNO guarantees the quality of all its products in accordance with the current General Terms and Conditions of Sale. Industrias JUNO, S.A. Barrio Sakoni, 10 - 48950 Erandio (Bizkaia) - Tel: +34 944 670 062 - Email: [infoweb@juno.es][mailto:infoweb@juno.es] Website: www.juno.es