

Technical Datasheets

JUNO PLASTER



Product Code: 77000 Plasters and fillers

DESCRIPTION

Shrink and crack-resistant powder filler for interior repairs.

USE: INTERIOR

Recommended for removing imperfections on wall surfaces and for preparing them for wallpapering or painting. Hides imperfections, grooves, cracks etc.

PROPERTIES

- Smooth flat surface finish
- Smooths and removes surface imperfections
- Does not shrink or crack
- Easy to mix
- Easy to apply
- Easy to sand
- Good hardness and resistance
- Excellent adhesion and cohesion

Type: Powder Filler

Colour: White

Density: Approx. 0.75 ± 0,05 g/cc

Working time (20 °C): Approx. 3 hours

Drying time: Variable depending on substrate and thickness

Maximum thickness per coat: 5 mm

Sanding/Painting: Once dry

Dilution: Water

Theoretical coverage: 1 m²/Kg/mm thickness

77000 WHITE



Formats: 1kg/ 5kg / 15 kg

Technical Datasheets

JUNO PLASTER



Product Code: 77000 Plasters and fillers

SURFACE PREPARATION

NEW SURFACES. Remove dust and clean the surface to be treated. Seal and protect metal parts with **Multisupport anticorrosive primer (Prod. Code 27.040)**. If the surface is very absorbent or disintegrating, seal with **Hidrocril (Prod.Code 81006)** thinned (1 part Hidrocril to 4 parts water).

APPLICATION TIPS

Surface must be solid, dry, free from dust, grease and wax.

Do not apply at temperatures below 5°C or above 35°C.

Do not apply on surfaces with permanent humidity.

Use the product within its workable time. After this time, the product will not behave nor provide expected results.

MIXTURE PREPARATION: Prepare the PLASTER in the ratio of 2.5 parts powder to 1 part water. Gradually pour the powder into water, stirring until a homogeneous paste is obtained for immediate use. This paste can be used for approximately 3 hours at 20°C once mixed.

APPLICATION METHOD. Apply with trowel or spatula.

CLEANING. Clean work tools with water immediately after use.

SAFETY AND ENVIRONMENT

Minimize product waste by estimating the necessary quantity, taking into account the m², porosity and texture of the substrate. Store the excess material in a ventilated and dry place. The container should be clean and sized for the amount of leftover product.

Close containers carefully and keep upright to avoid spillage. Preserve the containers from humidity and high temperatures. Recover unused product for a new use and reduce environmental effects. Do not eat, drink, or smoke during the preparation and application of the product. Surface preparation and application operations must be carried out with the corresponding safety measures.

For more information consult the Safety Data Sheet. In case of contact with the eyes, wash with plenty of clean water. Keep out of the reach of children. Do not discharge into drains or the environment. Dispose of at an authorized waste collection point.

Consult your city council about the correct recycling of both the container and the waste and leftover paint in accordance with the law and principles of environmental respect.