

Technical Datasheet

READY-MIX FILLER



Product Code: 77200 Plasters and fillers

DESCRIPTION

Tintable ready-mix repair filler. Smooth ready to use finish filler with excellent adhesion. Composed of water-soluble polymers and selected mineral fillers.

USE: INTERIOR

Recommended for repairing surface defects and smoothing interior surfaces before painting or wallpapering.

Usable on interior substrates made of plaster, plasterboard, plastic paints, smooth concrete, aerated concrete etc.

PROPERTIES

- Excellent adhesion a to substrates
- For all stages of plasterboard jointing and finishing
- Easy to apply
- Easy to sand
- White
- Fine finish

Type: Ready to use paste

Colour: White Tintable with Juno Universal colourant (max. 3%)

Density: Aprox. $1.75 \pm 0,05$ g/cc

Grain size: < 200 μ (Fine)

Working time (20°C): Unlimited

Drying time: Aprox. 8 hrs/mm, depending on thickness and ambient conditions

Max. thickness per coat: 2 mm

Sanding/repainting: Once dry/ 24 hours

Thinner: Water

Theoretical consumption: 1.75 kg/m²/mm thickness

Tinting: Juno Universal Colourant (max 3%)

77200 WHITE



Format: 0,5kg / 1 kg

Technical Datasheet

READY-MIX FILLER



Product Code: 77200 Plasters and fillers

SURFACE PREPARATION

NEW SURFACES. Remove dust and clean the surface to be treated. Seal and protect metal parts with **Multisupport anti-corrosive primer (Prod. Code 27.040)**. If the surface is very absorbent or disintegrating, seal with Hidrocril (Prod.Code 81006) thinned (1 part Hidrocril to 4 parts water).

APPLICATION TIPS

Surface must be solid, dry, free from dust, grease and wax. Do not apply at temperatures below 5°C or above 35°C. Do not apply on surfaces with permanent humidity. Use the product within its workable time. After this time, the product will not behave nor provide expected results.

APPLICATION METHOD. Apply with trowel or spatula. The working time is unlimited. Once the support is dry, sand, dust and paint.

CLEANING. Clean work tools with water immediately after use.

SAFETY AND ENVIRONMENT

Minimize product waste by estimating the necessary quantity, taking into account the m², porosity and texture of the substrate. Store the excess material in a ventilated and dry place. The container should be clean and sized for the amount of leftover product.

Close containers carefully and keep upright to avoid spillage. Preserve the containers from humidity and high temperatures. Recover unused product for a new use and reduce environmental effects. Do not eat, drink, or smoke during the preparation and application of the product. Surface preparation and application operations must be carried out with the corresponding safety measures.

For more information consult the Safety Data Sheet. In case of contact with the eyes, wash with plenty of clean water. Keep out of the reach of children. Do not discharge into drains or the environment. Dispose of at an authorized waste collection point.

Consult your city council about the correct recycling of both the container and the waste and leftover paint in accordance with the law and principles of environmental respect.