

Technical Datasheet

Cover-All Plaster



Product Code: 77406 Plasters and Caulk

DESCRIPTION

Interior use powder plaster for preparing substrates before painting or wall papering.

USE: INTERIOR

Recommended for smoothing and leveling walls with decorative finishes, drop type, pitted, etc.

For the removal of small imperfections in order to prepare them for wallpaper or painting. Usable on interior plaster, plasterboard, plasterboard, emulsion paints, smooth concrete, aerated concrete etc.

PROPERTIES

- Good adhesion on painted surfaces
- Fine smooth finish
- Easy sanding
- Tough hardwearing finish

Type: Powder

Colour: White

Density: Approx. 0.95 ± 0,05 g/cc

Work time (20 °C): Approx 24 hours

Drying time: Approx. 12 hrs/mm, Depending on thickness

Max. thickness per coat: 5 mm

Sanding/Painting: Once dry

Diluent/Thinner/Mix: Water

Theoretical coverage: 1 m²/Kg/mm thickness

77406 WHITE



Format: 15 kg

The information contained in this technical sheet may change and must be updated. See www.juno.es or your nearest JUNO representative for the latest data sheet. Technical application advice, whether verbal, in writing or through testing, is based on JUNO's technical knowledge and experience. The data shown in this document should be considered a recommendation and as such does not imply any commitment, even with regard to possible industrial property rights of third parties. The application, use and transformation of the products supplied by JUNO are carried out by third parties. Consequently, the final result is the sole responsibility of the customer, applicator or handler of the products and not of the supplying company. This document does not exempt the client from carrying out his own examination of the products supplied, in order to verify their suitability for the procedures and purposes foreseen. In the event of liability assumed by JUNO, it will be limited to the strict value of the merchandise supplied and used by the customer, whatever the damages caused.

JUNO guarantees the quality of all its products, in accordance with the General Conditions of Sale in force.
Industrias JUNO, S.A. • Barrio Sakoni, 10 • 48950 Erandio (Bizkaia) • Tel. 944 670 062 • infoweb@juno.es • www.juno.es

Technical Datasheet

Cover-All Plaster



Product Code: 77406 Plasters and Caulk

SURFACE PREPARATION

NEW SURFACES. Eliminate dust and clean the surface to be treated. Prime and protect any metal parts with Multisupport anticorrosive primer (Cod 27.040). If the base is very absorbent or disintegrable, prime with Hidrocril (Cod 81006) thinned with (1 part of Hidrocril / 4 parts of water).

PRE-PAINTED SURFACES. On glossy surfaces it is recommended to sand and remove dust beforehand.

APPLICATION TIPS

The surface must be sound, dry, free from dust, grease and wax.

Do not apply at temperatures below 5°C, or above 35°C.

Do not apply on substrates subjected to permanent humidity.

Use the product within its useful life. After this time, unfavorable properties can be obtained.

MIXTURE PREPARATION. Prepare the mix in the ratio of 2.5 parts of powder to 1 part water.

Mix thoroughly so that a smooth and consistent paste is obtained, for immediate use.

This paste can be used for approximately 24 hours after mixing.

APPLICATION METHOD. Apply with a trowel or spatula. For large thicknesses it is recommended to apply it in successive layers, once previous coat has dried. Once the support is dry, sand, remove/clean dust and paint.

CLEANING. Clean work tools with water immediately after use.

SAFETY & ENVIRONMENT

Minimize product waste by estimating the necessary amount, taking into account the m², porosity and texture of the support.

Store the excess material in a ventilated and dry place. The container should be clean and sized for the amount of leftover product. Close containers carefully and keep upright to avoid spillage. Preserve the containers from humidity and high temperatures. Recover unused product for a new use and reduce environmental effects.

Do not eat, drink, or smoke during the preparation and application of the product. Surface preparation and application operations must be carried out with the corresponding safety measures. For more information consult the Safety Data Sheet.

In case of contact with the eyes, wash with plenty of clean water. Keep out of the reach of children.

Do not discharge into drains or the environment. Dispose of at an authorized waste collection point. Consult your city council about the correct recycling of both the container and the waste and leftover paint in accordance with the law and principles of environmental respect.