

# Technical Datasheets

## SANDABLE FILLER



Product Code: 77410 Plasters and fillers

### DESCRIPTION

Powder wall preparation filler for both bulk filling and finishing textured/rough interior surfaces. Composed of water-soluble polymers and selected mineral fillers.

### USE: INTERIOR

Ideal versatile filler suitable for a variety of jobs. Recommended for removing imperfections on wall surfaces and for preparing them for wallpapering or painting. Ideal for repairs, chasing in and patching. Hides imperfections, grooves, cracks etc.

### PROPERTIES

- Smooth finish
- Great filling capacity
- Excellent adhesion, even on painted surfaces
- Fine granulometry
- Easy application
- Easy sanding

**Type:** Powder Filler

**Colour:** White

**Grain size:** < 200µ (Fine)

**Working time (20 °C):** 3 hours

**Drying time:** 6 hrs./mm. Thickness and temperature dependant.

**Maximum thickness per coat:** 5 mm

**Sanding/Painting:** Once dry

**Dilution:** 0.5L Water/1Kg. Powder

**Theoretical coverage:** 0.95 m<sup>2</sup>/Kg/mm thickness

77410 WHITE



Format: 15 kg

# Technical Datasheets

## SANDABLE FILLER



Product Code: 77410 Plasters and fillers

### SURFACE PREPARATION

**NEW SURFACES.** Remove dust and clean the surface to be treated. Seal and protect metal parts with **Multisupport anticorrosive primer (Prod. Code 27.040)**. If the surface is very absorbent or disintegrating, seal with **Hidrocril (Prod.Code 81006)** thinned (1 part Hidrocril to 4 parts water).

### APPLICATION TIPS

Surface must be solid, dry, free from dust, grease and wax.

Do not apply at temperatures below 5°C or above 35°C.

Do not apply on surfaces with permanent humidity.

Use the product within its workable time. After this time, the product will not behave nor provide expected results.

**MIXTURE PREPARATION:** Prepare the PLASTER in the ratio of 0.5L water per 1 kg. powder. Mix until a homogeneous paste is obtained for immediate use. Filler can be used for approximately 3 hours once mixed.

**APPLICATION METHOD.** Apply with trowel or spatula. To reach higher thicknesses, it is recommended to apply gradually in successive coats, making sure prior layer is fully dry. Once the surface is dry, sand, clean dust and paint.

**CLEANING.** Clean work tools with water immediately after use.

### SAFETY AND ENVIRONMENT

Minimize product waste by estimating the necessary quantity, taking into account the m<sup>2</sup>, porosity and texture of the substrate. Store the excess material in a ventilated and dry place. The container should be clean and sized for the amount of leftover product.

Close containers carefully and keep upright to avoid spillage. Preserve the containers from humidity and high temperatures. Recover unused product for a new use and reduce environmental effects. Do not eat, drink, or smoke during the preparation and application of the product. Surface preparation and application operations must be carried out with the corresponding safety measures.

For more information consult the Safety Data Sheet. In case of contact with the eyes, wash with plenty of clean water. Keep out of the reach of children. Do not discharge into drains or the environment. Dispose of at an authorized waste collection point.

Consult your city council about the correct recycling of both the container and the waste and leftover paint in accordance with the law and principles of environmental respect.